

## Radio Test Report

**Report No.:** RJBARR-WTW-P21100969L

**Test Model:** MT7902

**Received Date:** 2023/5/8

**Issued Date:** 2023/5/10

**Applicant:** MediaTek Inc.

**Address:** No. 1, Dusing 1st Rd., Hsinchu Science Park, Hsinchu City, 30078 Taiwan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan

**Test Location:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

Release Control Record .....	3
1 Certificate of Conformity .....	4
2 General Information .....	5
2.1 General Description of EUT .....	5
Appendix - Information of the Testing Laboratories .....	36



Release Control Record

Issue No.	Description	Date Issued
RJBARR-WTW-P21100969L	Original release	2023/5/10

## 1 Certificate of Conformity

**Product:** 1TX 11ax (WiFi6E) BW160 + BT/BLE Combo Card

**Brand:** MediaTek

**Test Model:** MT7902

**Applicant:** MediaTek Inc.

**Standards:** ARIB STD-T66 (V3.7),  
MIC No.88(2004) Test method of specified radio equipments  
Annex no. 43 Article 2 paragraph 1 item (19)  
RCR STD-33 (V5.4),  
MIC No.88(2004) Test method of specified radio equipments  
Annex no. 44 Article 2 paragraph 1 item (19)-2  
Certification Ordinance Article 2-1-19-3  
Certification Ordinance Article 2-1-79  
Certification Ordinance Article 2-1-80

This report is issued as a supplementary report. This report shall be used combined together with its original report.

**Prepared by :** Vito Lung , **Date:** 2023/5/10  
Vito Lung / Specialist

**Approved by :** May Chen , **Date:** 2023/5/10  
May Chen / Manager

## 2 General Information

### 2.1 General Description of EUT

Product	1TX 11ax (WiFi6E) BW160 + BT/BLE Combo Card
Brand	MediaTek
Test Model	MT7902
Nominal Voltage	3.3Vdc from host equipment
Modulation Type	<b>For WLAN</b> CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT in 2.4GHz 1024QAM for OFDMA in 11ax mode <b>For BT-EDR:</b> GFSK, $\pi/4$ -DQPSK, 8DPSK <b>For BT-LE:</b> GFSK
Modulation Technology	<b>For WLAN:</b> DSSS, OFDM, OFDMA <b>For BT-EDR:</b> FHSS <b>For BT-LE:</b> DTS
Transfer Rate	<b>For WLAN:</b> 802.11b: up to 11 Mbps 802.11a/g: up to 54 Mbps 802.11n: up to 150 Mbps 802.11ac: up to 866.7 Mbps 802.11ax: up to 1201.0 Mbps <b>For BT-EDR:</b> Up to 3 Mbps <b>For BT-LE:</b> Up to 2 Mbps
Operating Frequency	<b>For WLAN:</b> <b>2.4GHz:</b> 802.11b: 2412 ~ 2484 MHz 802.11g/n (HT20), VHT20, 802.11ax (HE20): 2412 ~ 2472 MHz 802.11n (HT40), VHT40, 802.11ax (HE40): 2422 ~ 2462 MHz <b>5GHz:</b> 802.11a/n/ac/ax (W52+W53): 5180 ~ 5320 MHz 802.11a/n/ac/ax (W56): 5500 ~ 5720 MHz <b>6GHz:</b> 5955 ~ 6415 MHz <b>For BT:</b> 2402 ~ 2480 MHz
Number of Channel	<b>For WLAN</b> <b>2.4GHz:</b> 802.11b: 14 802.11g/n (HT20), VHT20, 802.11ax (HE20): 13 802.11n (HT40), VHT40, 802.11ax (HE40): 9 <b>5GHz: (W52+W53)</b> 802.11a/n (HT20)/ac (VHT20), 802.11ax (HE20): 8 802.11n (HT40)/ac (VHT40), 802.11ax (HE40): 4 802.11ac (VHT80), 802.11ax (HE80): 2 802.11ac (VHT160), 802.11ax (HE160): 1 <b>5GHz: (W56)</b> 802.11a/n (HT20)/ac (VHT20), 802.11ax (HE20): 12 802.11n (HT40)/ac (VHT40), 802.11ax (HE40): 6 802.11ac (VHT80), 802.11ax (HE80): 3 802.11ac (VHT160), 802.11ax (HE160): 1 <b>6GHz:</b> 802.11a, 802.11ax (HE20): 24



	802.11ax (HE40): 12 802.11ax (HE80): 6 802.11ax (HE160): 3 <b>For BT-EDR: 79</b> <b>For BT-LE: 40</b>
Antenna Type	Refer to note
Antenna Connector	Refer to note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. This report is issued as a supplementary report to BV CPS report as below test report:

Function	Report No.
WLAN_2.4GHz	RJBARR-WTW-P21100969J
WLAN_5GHz	
BT-EDR	
BT-LE	
WLAN_6GHz (LPI)	
WLAN_6GHz (VLP)	

2. The difference compared with original report is adding antennas and according to EUT's specification by the customer judgement, there is no additional tested.

Original								
Antenna Set No	RF Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
1	Chain0	PSA	RFMTA340718EMLB302	3.18	2.4~2.4835	PIFA	ipex(MHF)	200
				4.92	5.15~5.895			
	Chain1	PSA	RFMTA340718EMLB302	3.18	2.4~2.4835	PIFA	ipex(MHF)	200
				4.92	5.15~5.895			
2	Chain0	PSA	RFMTA311020EB301	1.71	2.4~2.4835	PIFA	ipex(MHF)	200
				4.82	5.15~5.895			
				4.76	5.925~6.425			
				4.29	6.425~6.525			
				4.61	6.525~6.875			
	Chain1	PSA	RFMTA311020EB301	4.09	6.875~7.125	PIFA	ipex(MHF)	200
				1.71	2.4~2.4835			
				4.82	5.15~5.895			
				4.76	5.925~6.425			
				4.29	6.425~6.525			
				4.61	6.525~6.875			
				4.09	6.875~7.125			

Ant. Set	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
3	LUXSHARE-ICT	Main	LA9RF361-CS-H	2.98 dBi @ 2.4GHz 4.92dBi @ 5GHz	0.66 dB @2.4GHz 1.06 dB @5GHz	PIFA	I-PEX	275
		Aux	LA9RF362-CS-H	2.78 dBi @ 2.4GHz 2.59 dBi @ 5GHz	1.26 dB @2.4GHz 1.95dB @5GHz			520
4	AWAN	Main	AYF6Y-100190	2.88 dBi @ 2.4GHz 4.82 dBi @ 5GHz	0.69 dB @2.4GHz 1.17 dB @5GHz	PIFA	IPEX NGFF	275
		Aux	AYF6Y-100191	2.64 dBi @ 2.4GHz 2.47 dBi @ 5GHz	1.3 dB @2.4GHz 2.21 dB @5GHz			520

Ant. Set	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
5	INPAQ	Main	WA-P-LE-02-064	2.75 dBi @ 2.4GHz 4.57 dBi @ 5.15~5.85GHz	0.56 dB @2.4GHz 0.87 dB @ 5.15~5.85GHz	PIFA	I-PEX MHF4-L	200
		Aux	WA-P-LE-01-006	2.71 dBi @ 2.4GHz 4.63 dBi @ 5.15~5.85GHz	1.22 dB @2.4GHz 1.90 dB @5.15~5.85GHz			440
6	PULSE	Main	TZ20921	2.55 dBi @ 2.4GHz 4.33 dBi @ 5.15~5.85GHz	0.60 dB @2.4GHz 0.85 dB @5.15~5.85GHz	PIFA	I-PEX	200
		Aux	TZ20924	2.22 dBi @ 2.4GHz 4.15 dBi @5.15~5.85GHz	1.33 dB @2.4GHz 1.86 dB @5.15~5.85GHz			440



Ant. Set	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
7	WNC	Main	81EABU15.G37 (DC33002R700)	2.23 dBi @ 2.4GHz 0.46 dBi @ 5GHz	1.56 dB @2.4GHz 2.23 dB @5GHz	PIFA	I-pex MHF-4L	608.5
		Aux	81EABU15.G38 (DC33002R710)	1.69 dBi @ 2.4GHz 0.02 dBi @ 5GHz	2.09 dB @2.4GHz 2.97 dB @5GHz			813.5
8	WNC	Main	81EABU15.G53	2.43dBi @ 2.4GHz 2.01dBi @ 5GHz	2.12 dB @2.4GHz 3.28dB @5GHz	PIFA	i-pex(MHF)	587
		Aux	81EABU15.G53	2.84dBi @ 2.4GHz 1.26dBi @ 5GHz	2.73 dB @2.4GHz 4.22dB @5GHz			757

Ant. Set	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
9	INPAQ	Main:12CR5-1ANTA2-51R (DAM-J8-K1-DB-800-10-25)	Main:12CR5-1ANTA2-51R (DAM-J8-K1-DB-800-10-25)	2.32dBi @ 2.4GHz 2.82dBi @ 5GHz 2.97 dBi @ 5.925~6.425GHz 2.64 dBi @6425~6525GHz 2.64 dBi @6.525~6.875GHz 2.57 dBi @6.875~7.125GHz	1.62 dB @2.4GHz 2.69dB @5GHz 2.87 dB@ 5.925~6.425GHz 2.90 dB @6425~6525GHz 3.02 dB @6.525~6.875GHz 3.15 dB @6.875~7.125GHz	PIFA	SMA RP PLUG	800
		Aux:12CR5-1ANTA2-51R (DAM-J8-K1-DB-800-10-25)	Aux:12CR5-1ANTA2-51R (DAM-J8-K1-DB-800-10-25)	2.38 dBi @ 2.4GHz 2.97 dBi @ 5GHz 2.98 dBi @ 5.925~6.425GHz 2.96 dBi @6425~6525GHz 2.84 dBi @6.525~6.875GHz 2.82 dBi @6.875~7.125GHz	1.7 dB @2.4GHz 2.51dB @5GHz 2.87 dB@ 5.925~6.425GHz 2.90 dB @6425~6525GHz 3.02 dB @6.525~6.875GHz 3.15 dB @6.875~7.125GHz			800
10	INPAQ	Main:12CR5-1ANTA2-61R (DAM-J9-K1-DB-800-10-70)	12CR5-1ANTA2-61R (DAM-J9-K1-DB-800-10-70)	2.25 dBi @ 2.4GHz 2.79 dBi @ 5GHz 2.89 dBi @ 5.925~6.425GHz 2.94 dBi @6425~6525GHz 2.95 dBi @6.525~6.875GHz 2.97 dBi @6.875~7.125GHz	1.58 dB @2.4GHz 2.61dB @5GHz 2.87 dB@ 5.925~6.425GHz 2.90 dB @6425~6525GHz 3.02 dB @6.525~6.875GHz 3.15 dB @6.875~7.125GHz	PIFA	SMA RP PLUG	800
		Aux:12CR5-1ANTA2-61R (DAM-J9-K1-DB-800-10-70)	12CR5-1ANTA2-61R (DAM-J9-K1-DB-800-10-70)	2.30 dBi @ 2.4GHz 2.99 dBi @ 5GHz 2.85 dBi @ 5.925~6.425GHz 3.09 dBi @6425~6525GHz 3.11 dBi @6.525~6.875GHz 3.14 dBi @6.875~7.125GHz	1.7 dB @2.4GHz 2.61dB @5GHz 2.87 dB@ 5.925~6.425GHz 2.90 dB @6425~6525GHz 3.02 dB @6.525~6.875GHz 3.15 dB @6.875~7.125GHz			800

Ant. Set	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
11	ASUS	Main	14008-02650000	1.64@2.4~2.4835GHz 1.15@5.15~5.85GHz	2.2dB @2.4GHz 4.0dB @5GHz	Dipole	SMA RP PLUG(RF Cable : IPEX MHF4)	800
		Aux	14008-02650000	1.65@2.4~2.4835GHz 1.12@5.15~5.85GHz	2.2dB @2.4GHz 4.0dB @5GHz	Dipole	SMA RP PLUG(RF Cable : IPEX MHF4)	800
12	ASUS	Main	14008-02650400	0.4@2.4~2.4835GHz 0.1@5.15~5.85GHz	2.21dB @2.4GHz 3.54dB @5GHz	Dipole	SMA RP PLUG(RF Cable : IPEX MHF4)	800
		Aux	14008-02650400	-0.8@2.4~2.4835GHz 2.7@5.15~5.85GHz	2.21dB @2.4GHz 3.54dB @5GHz	Dipole	SMA RP PLUG(RF Cable : IPEX MHF4)	800

Ant. Set	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
13	ASUS	Main	14008-02650600	1.23@2.4~2.4835GHz 3.93@5.15~5.85GHz	1.84dB @2.4GHz 4.21dB @5GHz	Dipole	SMA R/P PLUG (RF Cable : IPEX)	800
		Aux	14008-02650600	-0.1@2.4~2.4835GHz 4.55@5.15~5.85GHz	1.75dB @2.4GHz 3.97dB @5GHz	Dipole	SMA R/P PLUG (RF Cable : IPEX)	800
14	Cortec	Main	AN2450-4902BRS	2.92@2.4~2.4835GHz 4.67@5.15~5.85GHz	0.5 dB @2.4GHz 0.8 dB @5GHz	Dipole	SMA R/P PLUG (RF Cable : IPEX)	150
	Cortec	Aux	AN2450-4902BRS	2.92@2.4~2.4835GHz 4.67@5.15~5.85GHz	0.5 dB @2.4GHz 0.8 dB @5GHz	Dipole	SMA R/P PLUG (RF Cable : IPEX)	150

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
15	INPAQ	Main	WA-P-LE-02-157 (14008-05600200)	2.88 dBi @ 2.4GHz 3.08dBi @ 5GHz 2.55 dBi @ 5.925~6.425GHz 3.12 dBi @6.425~6.525GHz 4.00 dBi @6.525~6.875GHz 3.83 dBi @6.875~7.125GHz	0.5 dB @2.4G 0.75 dB @5G 0.82 dB @ 5.925~6.425GHz 0.83 dB @6.425~6.525GHz 0.85 dB @6.525~6.875GHz 0.88 dB @6.875~7.125GHz	PIFA	IPEX MHF4-L	180	DIV
		Aux	WA-P-LE-01-046 (14008-05600300)	2.83 dBi @ 2.4GHz 2.12 dBi @ 5GHz 1.05 dBi @ 5.925~6.425GHz 1.94 dBi @6.425~6.525GHz 3.21 dBi @6.525~6.875GHz 3.21 dBi @6.875~7.125GHz	1.96 dB @2.4G 2.99 dB @5G 3.21 dB @ 5.925~6.425GHz 3.29 dB @6.425~6.525GHz 3.38 dB @6.525~6.875GHz 3.49 dB @6.875~7.125GHz			545	



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
16	Luxshare-ICT	Main	LA9RF474-CS-H (14008-05600000)	2.32 dBi @ 2.4GHz 2.85 dBi @ 5GHz 2.50 dBi @ 5.925~6.425GHz 3.03 dBi @ 6.425~6.525GHz 3.87 dBi @ 6.525~6.875GHz 3.81 dBi @ 6.875~7.125GHz	0.49 dB @2.4G 0.76 dB @5G 0.79 dB @ 5.925~6.425GHz 0.79 dB @ 6.425~6.525GHz 0.80 dB @ 6.525~6.875GHz 0.80 dB @ 6.875~7.125GHz	PIFA	IPEX :205 65-001R-13	180	DIV
		Aux	LA9RF475-CS-H (14008-05600100)	2.81 dBi @ 2.4GHz 1.63 dBi @ 5GHz 1.03 dBi @ 5.925~6.425GHz 1.92 dBi @ 6.425~6.525GHz 2.46 dBi @ 6.525~6.875GHz 3.09 dBi @ 6.875~7.125GHz	1.34 dB @2.4G 2.10 dB @5G 2.18 dB @ 5.925~6.425GHz 2.18 dB @ 6.425~6.525GHz 2.20 dB @ 6.525~6.875GHz 2.21 dB @ 6.875~7.125GHz			545	
17	INPAQ	Main	WA-P-LE-02-128 (14008-05590200)	2.6 dBi @ 2.4GHz 4.16 dBi @ 5GHz 3.71dBi @ 5.925~6.425GHz 3.55 dBi @ 6.425~6.525GHz 3.95 dBi @ 6.525~6.875GHz 3.5 dBi @ 6.875~7.125GHz	0.57 dB @2.4G 0.87 dB @5G 0.93 dB @ 5.925~6.425GHz 0.95 dB @ 6.425~6.525GHz 0.97 dB @ 6.525~6.875GHz 1 dB @ 6.875~7.125GHz	PIFA	IPEX MHF-4L	205	DIV
		Aux	WA-P-LE-01-034 (14008-05590300)	2.43 dBi @ 2.4GHz 3.18 dBi @ 5GHz 1.95 dBi @ 5.925~6.425GHz 1.63 dBi @ 6.425~6.525GHz 2.67 dBi @ 6.525~6.875GHz 3.1 dBi @ 6.875~7.125GHz	1.98 dB @2.4G 2.92 dB @5G 3.24 dB @ 5.925~6.425GHz 3.32 dB @ 6.425~6.525GHz 3.41 dB @ 6.525~6.875GHz 3.53 dB @ 6.875~7.125GHz			550	



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
18	Luxshare-ICT	Main	LA9RF438-CS-H (14008-05590000)	2.87 dBi @ 2.4GHz 4.37 dBi @ 5GHz 4.17 dBi @ 5.925~6.425GHz 3.82 dBi @6.425~6.525GHz 4.09 dBi @6.525~6.875GHz 3.76 dBi @6.875~7.125GHz	0.55 dB @2.4G 0.86 dB @5G 0.88 dB @ 5.925~6.425GHz 0.91 dB @6.425~6.525GHz 0.91 dB @6.525~6.875GHz 0.92 dB @6.875~7.125GHz	PIFA	IPEX MHF-4L	205	DIV
		Aux	LA9RF439-CS-H (14008-05590100)	2.86 dBi @ 2.4GHz 3.33dBi @ 5GHz 2.23 dBi @ 5.925~6.425GHz 2.12 dBi @6.425~6.525GHz 3.08 dBi @6.525~6.875GHz 3.35 dBi @6.875~7.125GHz	1.62 dB @2.4G 2.49 dB @5G 2.69 dB @ 5.925~6.425GHz 2.76 dB @6.425~6.525GHz 2.81 dB @6.525~6.875GHz 2.85 dB @6.875~7.125GHz			550	
19	INPAQ	Main	HQ20604864000 (WA-P-LE-02-071)	2.49dBi @ 2.4GHz 3.3dBi @ 5GHz 2.78dBi @ 5.925~6.425GHz 1.03 dBi @6.425~6.525GHz 1.54 dBi @6.525~6.875GHz 1.28 dBi @6.875~7.125GHz	0.6 dB @2.4G 0.89 dB @5G 0.98 dB @ 5.925~6.425GHz 1 dB @6.425~6.525GHz 1.02 dB @6.525~6.875GHz 1.05 dB @6.875~7.125GHz	PIFA	IPEX MHF-4L	216	DIV
		Aux	HQ20604863000 (WA-P-LE-03-003)	2.45 dBi @ 2.4GHz 2.99 dBi @ 5GHz 2.34 dBi @ 5.925~6.425GHz 1.93 dBi @6.425~6.525GHz 2.66 dBi @6.525~6.875GHz 2.87 dBi @6.875~7.125GHz	1.06 dB @2.4G 1.58 dB @5G 1.77 dB @ 5.925~6.425GHz 1.81 dB @6.425~6.525GHz 1.87 dB @6.525~6.875GHz 1.74 dB @6.875~7.125GHz			383	

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
20	INNOWAVE Corporation	Main	F00168007110001 (HQ20604865000)	2.88dBi @ 2.4GHz 3.93dBi @ 5GHz 2.82dBi @ 5.925~6.425GHz 3.69dBi @6.425~6.525GHz 4.53dBi @6.525~6.875GHz 3.42dBi @6.875~7.125GHz	0.55 dB @2.4G 1.12 dB @5G 1.19 dB @ 5.925~6.425GHz 1.23 dB @6.425~6.525GHz 1.27 dB @6.525~6.875GHz 1.06 dB @6.875~7.125GHz	PIFA	IPEX MHF-4L	216	DIV
		Aux	F00168007510002 (HQ20604862000)	2.77 dBi @ 2.4GHz 3.2 dBi @ 5GHz 2.5 dBi @ 5.925~6.425GHz 2.94 dBi @6.425~6.525GHz 2.89 dBi @6.525~6.875GHz 2.97 dBi @6.875~7.125GHz	1.08 dB @2.4G 1.75 dB @5G 1.91 dB @ 5.925~6.425GHz 2 dB @6.425~6.525GHz 2.05 dB @6.525~6.875GHz 2.1 dB @6.875~7.125GHz			383	
21	INPAQ	Main	WA-P-LE-02-113	2.33 dBi @ 2.4GHz 2.96 dBi @ 5GHz 4.23 dBi @ 5.925~6.425GHz 2.82 dBi @6.425~6.525GHz 3.63 dBi @6.525~6.875GHz 3.61 dBi @6.875~7.125GHz	0.57 dB @2.4G 0.85 dB @5G 0.93 dB @ 5.925~6.425GHz 0.95 dB @6.425~6.525GHz 0.98 dB @6.525~6.875GHz 1.01 dB @6.875~7.125GHz	PIFA	I-PEX MHF-4L	206	DIV
		Aux	WA-P-LE-03-010	2.06 dBi @ 2.4GHz 3.71 dBi @ 5GHz 3.09 dBi @ 5.925~6.425GHz 3.09 dBi @6.425~6.525GHz 2.61 dBi @6.525~6.875GHz 3.07 dBi @6.875~7.125GHz	0.88 dB @2.4G 1.35 dB @5G 1.44 dB @ 5.925~6.425GHz 1.47 dB @6.425~6.525GHz 1.5 dB @6.525~6.875GHz 1.55 dB @6.875~7.125GHz			317	

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
22	INNOWAVE Corporation	Main	F00192307110001 (HQ2060508L000)	1.46 dBi @ 2.4GHz 2.84 dBi @ 5GHz 1.72 dBi @ 5.925~6.425GHz 2.2 dBi @6.425~6.525GHz 2.2 dBi @6.525~6.875GHz 3.29 dBi @6.875~7.125GHz	0.52 dB @2.4G 0.96 dB @5G 1.03 dB @ 5.925~6.425GHz 1.08 dB @6.425~6.525GHz 1.1 dB @6.525~6.875GHz 1.15 dB @6.875~7.125GHz	PIFA	IPEX MHF-4L	206	DIV
		Aux	F00192307510002 (HQ2060508K000)	0.9 dBi @ 2.4GHz 1.67 dBi @ 5GHz 1.98 dBi @ 5.925~6.425GHz 1.98 dBi @6.425~6.525GHz 2.55 dBi @6.525~6.875GHz 3.02 dBi @6.875~7.125GHz	0.79 dB @2.4G 1.49 dB @5G 1.59 dB @ 5.925~6.425GHz 1.66 dB @6.425~6.525GHz 1.67 dB @6.525~6.875GHz 1.77 dB @6.875~7.125GHz			317	

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
23	INPAQ Corporation	Main	WA-P-LE-02-083 (HQ20604916000) (Platform type:K6502V)	2.91 dBi @ 2.4GHz 3.95 dBi @ 5GHz 4.25 dBi @ 5.925~6.425GHz 3.76 dBi @6.425~6.525GHz 4.26 dBi @6.525~6.875GHz 3.28 dBi @6.875~7.125GHz	0.53 dB @2.4G 0.82 dB @5G 0.92 dB @ 5.925~6.425GHz 0.92 dB @6.425~6.525GHz 0.96 dB @6.525~6.875GHz 1.01 dB @6.875~7.125GHz	PIFA	IPEX MHF-4L	190	DIV
		Aux	WA-P-LE-03-008 (HQ20604917000) (Platform type:K6502V)	2.94 dBi @ 2.4GHz 4.46 dBi @ 5GHz 4.29 dBi @ 5.925~6.425GHz 4.06 dBi @6.425~6.525GHz 4.32 dBi @6.525~6.875GHz 3.09 dBi @6.875~7.125GHz	1.01 dB @2.4G 1.56 dB @5G 1.75 dB @ 5.925~6.425GHz 1.75 dB @6.425~6.525GHz 1.82 dB @6.525~6.875GHz 1.93 dB @6.875~7.125GHz			362	
		Main	WA-P-LE-02-083 (HQ20604916000) (Platform type:K6602V)	2.92 dBi @ 2.4GHz 4.46 dBi @ 5GHz 4.1 dBi @ 5.925~6.425GHz 4.2 dBi @6.425~6.525GHz 4.13 dBi @6.525~6.875GHz 3.68 dBi @6.875~7.125GHz	0.53 dB @2.4G 0.82 dB @5G 0.92 dB @ 5.925~6.425GHz 0.92 dB @6.425~6.525GHz 0.96 dB @6.525~6.875GHz 1.01 dB @6.875~7.125GHz			190	
		Aux	WA-P-LE-03-008 (HQ20604917000) (Platform type:K6602V)	2.62 dBi @ 2.4GHz 3.72 dBi @ 5GHz 4.44 dBi @ 5.925~6.425GHz 4.02 dBi @6.425~6.525GHz 4.5 dBi @6.525~6.875GHz 3.98 dBi @6.875~7.125GHz	1.01 dB @2.4G 1.56 dB @5G 1.75 dB @ 5.925~6.425GHz 1.75 dB @6.425~6.525GHz 1.82 dB @6.525~6.875GHz 1.93 dB @6.875~7.125GHz			362	
	INPAQ Corporation	Main	WA-P-LE-02-083 (HQ20604916000) (Platform type:K6602V)	2.92 dBi @ 2.4GHz 4.46 dBi @ 5GHz 4.1 dBi @ 5.925~6.425GHz 4.2 dBi @6.425~6.525GHz 4.13 dBi @6.525~6.875GHz 3.68 dBi @6.875~7.125GHz	0.53 dB @2.4G 0.82 dB @5G 0.92 dB @ 5.925~6.425GHz 0.92 dB @6.425~6.525GHz 0.96 dB @6.525~6.875GHz 1.01 dB @6.875~7.125GHz	PIFA	IPEX MHF-4L	190	DIV
		Aux	WA-P-LE-03-008 (HQ20604917000) (Platform type:K6602V)	2.62 dBi @ 2.4GHz 3.72 dBi @ 5GHz 4.44 dBi @ 5.925~6.425GHz 4.02 dBi @6.425~6.525GHz 4.5 dBi @6.525~6.875GHz 3.98 dBi @6.875~7.125GHz	1.01 dB @2.4G 1.56 dB @5G 1.75 dB @ 5.925~6.425GHz 1.75 dB @6.425~6.525GHz 1.82 dB @6.525~6.875GHz 1.93 dB @6.875~7.125GHz			362	
		Main	WA-P-LE-02-083 (HQ20604916000) (Platform type:K6602V)	2.92 dBi @ 2.4GHz 4.46 dBi @ 5GHz 4.1 dBi @ 5.925~6.425GHz 4.2 dBi @6.425~6.525GHz 4.13 dBi @6.525~6.875GHz 3.68 dBi @6.875~7.125GHz	0.53 dB @2.4G 0.82 dB @5G 0.92 dB @ 5.925~6.425GHz 0.92 dB @6.425~6.525GHz 0.96 dB @6.525~6.875GHz 1.01 dB @6.875~7.125GHz			190	
		Aux	WA-P-LE-03-008 (HQ20604917000) (Platform type:K6602V)	2.62 dBi @ 2.4GHz 3.72 dBi @ 5GHz 4.44 dBi @ 5.925~6.425GHz 4.02 dBi @6.425~6.525GHz 4.5 dBi @6.525~6.875GHz 3.98 dBi @6.875~7.125GHz	1.01 dB @2.4G 1.56 dB @5G 1.75 dB @ 5.925~6.425GHz 1.75 dB @6.425~6.525GHz 1.82 dB @6.525~6.875GHz 1.93 dB @6.875~7.125GHz			362	

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)	Remark
24	INNOWAVE Corporation	Main	F00175607110001 (HQ20604919000) (Platform type:K6502V)	2.85 dBi @ 2.4GHz 3.43 dBi @ 5GHz 4.03 dBi @ 5.925~6.425GHz 3.3 dBi @ 6.425~6.525GHz 3.58 dBi @ 6.525~6.875GHz 3.62 dBi @ 6.875~7.125GHz	0.53 dB @2.4G 1.06dB @5G 1.12 dB @ 5.925~6.425GHz 1.14 dB @ 6.425~6.525GHz 1.21 dB @ 6.525~6.875GHz 1.23 dB @ 6.875~7.125GHz	PIFA	IPEX-20565	216	DIV
		Aux	F00175607510002 (HQ20604918000) (Platform type:K6502V)	2.82 dBi @ 2.4GHz 4.25 dBi @ 5GHz 3.89 dBi @ 5.925~6.425GHz 3.96 dBi @ 6.425~6.525GHz 4.18 dBi @ 6.525~6.875GHz 3.02 dBi @ 6.875~7.125GHz	1.02 dB @2.4G 1.72 dB @5G 1.88 dB @ 5.925~6.425GHz 1.97 dB @ 6.425~6.525GHz 2.01 dB @ 6.525~6.875GHz 2.05 dB @ 6.875~7.125GHz			383	
		Main	F00175607110001 (HQ20604919000) (Platform type:K6602V)	2.9 dBi @ 2.4GHz 3.47 dBi @ 5GHz 3.78dBi @ 5.925~6.425GHz 3.09 dBi @ 6.425~6.525GHz 3.39dBi @ 6.525~6.875GHz 3.36 dBi @ 6.875~7.125GHz	0.53 dB @2.4G 1.06 dB @5G 1.12 dB @ 5.925~6.425GHz 1.14 dB @ 6.425~6.525GHz 1.21 dB @ 6.525~6.875GHz 1.23 dB @ 6.875~7.125GHz			216	
		Aux	F00175607510002 (HQ20604918000) (Platform type:K6602V)	2.58 dBi @ 2.4GHz 3.03 dBi @ 5GHz 4.04 dBi @ 5.925~6.425GHz 3.97 dBi @ 6.425~6.525GHz 4.01dBi @ 6.525~6.875GHz 3.67 dBi @ 6.875~7.125GHz	1.02 dB @2.4G 1.72 dB @5G 1.88 dB @ 5.925~6.425GHz 1.97 dB @ 6.425~6.525GHz 2.01 dB @ 6.525~6.875GHz 2.05 dB @ 6.875~7.125GHz			383	
	INNOWAVE Corporation	Main	F00175607110001 (HQ20604919000) (Platform type:K6602V)	2.9 dBi @ 2.4GHz 3.47 dBi @ 5GHz 3.78dBi @ 5.925~6.425GHz 3.09 dBi @ 6.425~6.525GHz 3.39dBi @ 6.525~6.875GHz 3.36 dBi @ 6.875~7.125GHz	0.53 dB @2.4G 1.06 dB @5G 1.12 dB @ 5.925~6.425GHz 1.14 dB @ 6.425~6.525GHz 1.21 dB @ 6.525~6.875GHz 1.23 dB @ 6.875~7.125GHz	PIFA	IPEX-20565	216	DIV
		Aux	F00175607510002 (HQ20604918000) (Platform type:K6602V)	2.58 dBi @ 2.4GHz 3.03 dBi @ 5GHz 4.04 dBi @ 5.925~6.425GHz 3.97 dBi @ 6.425~6.525GHz 4.01dBi @ 6.525~6.875GHz 3.67 dBi @ 6.875~7.125GHz	1.02 dB @2.4G 1.72 dB @5G 1.88 dB @ 5.925~6.425GHz 1.97 dB @ 6.425~6.525GHz 2.01 dB @ 6.525~6.875GHz 2.05 dB @ 6.875~7.125GHz			383	
		Main	F00175607110001 (HQ20604919000) (Platform type:K6602V)	2.9 dBi @ 2.4GHz 3.47 dBi @ 5GHz 3.78dBi @ 5.925~6.425GHz 3.09 dBi @ 6.425~6.525GHz 3.39dBi @ 6.525~6.875GHz 3.36 dBi @ 6.875~7.125GHz	0.53 dB @2.4G 1.06 dB @5G 1.12 dB @ 5.925~6.425GHz 1.14 dB @ 6.425~6.525GHz 1.21 dB @ 6.525~6.875GHz 1.23 dB @ 6.875~7.125GHz			216	
		Aux	F00175607510002 (HQ20604918000) (Platform type:K6602V)	2.58 dBi @ 2.4GHz 3.03 dBi @ 5GHz 4.04 dBi @ 5.925~6.425GHz 3.97 dBi @ 6.425~6.525GHz 4.01dBi @ 6.525~6.875GHz 3.67 dBi @ 6.875~7.125GHz	1.02 dB @2.4G 1.72 dB @5G 1.88 dB @ 5.925~6.425GHz 1.97 dB @ 6.425~6.525GHz 2.01 dB @ 6.525~6.875GHz 2.05 dB @ 6.875~7.125GHz			383	



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
25	INPAQ	Main	WA-P-LELE-04-042	1.84dBi @ 2.4GHz 3.61dBi @ 5GHz 3.86 dBi @ 5.925~6.425GHz 3.87 dBi @6425~6525GHz 3.97 dBi @6.525~6.875GHz 3.42 dBi @6.875~7.125GHz	0.85 dB @2.4G 1.31dB @5G 1.40 dB @ 5.925~6.425GHz 1.43 dB @6425~6525GHz 1.46 dB @6.525~6.875GHz 1.50 dB @6.875~7.125GHz	PIFA	I-PEX MHF4-L	280
		Aux	WA-P-LELE-04-042	-0.76dBi @ 2.4GHz 2.55dBi @ 5GHz 2.53dBi @ 5GHz 3.13 dBi @ 5.925~6.425GHz 2.83 dBi @6425~6525GHz 2.44 dBi @6.525~6.875GHz 3.27 dBi @6.875~7.125GHz	0.85 dB @2.4G 1.31dB @5G 1.40 dB @ 5.925~6.425GHz 1.43 dB @6425~6525GHz 1.46 dB @6.525~6.875GHz 1.50 dB @6.875~7.125GHz			280
26	Pulse	Main	TZ2484W	2.90 dBi @ 2.4GHz 4.63 dBi @ 5GHz 4.54 dBi @ 5.925~6.425GHz 4.20 dBi @6425~6525GHz 4.20 dBi @6.525~6.875GHz 3.98 dBi @6.875~7.125GHz	0.78 dB @ 2.4GHz 1.23 dB @ 5GHz 1.21 dB @ 5GHz 1.27 dB @ 5.925~6.425GHz 1.31 dB @6425~6525GHz 1.34 dB @6.525~6.875GHz 1.38 dB @6.875~7.125GHz	PIFA	I-PEX	283
		Aux	TZ2484W	0.22 dBi @ 2.4GHz 3.24 dBi @ 5GHz 3.04dBi @ 5GHz 3.46 dBi @ 5.925~6.425GHz 2.97 dBi @6425~6525GHz 2.82 dBi @6.525~6.875GHz 3.49 dBi @6.875~7.125GHz	0.78 dB @ 2.4GHz 1.23 dB @ 5GHz 1.17 dB @ 5GHz 1.27 dB @ 5.925~6.425GHz 1.31 dB @6425~6525GHz 1.34 dB @6.525~6.875GHz 1.38 dB @6.875~7.125GHz			283



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
27	AWAN	Main	AYP6Y-200058	1.4 dBi @ 2.4GHz 2.84 dBi @ 5GHz 2.81 dBi @ 5.925~6.425GHz 1.63 dBi @6425~6525GHz 1.86 dBi @6.525~6.875GHz 1.01 dBi @6.875~7.125GHz	0.71 dB @2.4G 1.18 dB @5G 1.31 dB @ 5.925~6.425GHz 1.31 dB @6425~6525GHz 1.31 dB @6.525~6.875GHz 1.31 dB @6.875~7.125GHz	PIFA	IPEX NGFF	285
		Aux	AYP6Y-200058	1.27 dBi @ 2.4GHz 3.11 dBi @ 5GHz 1.48 dBi @ 5.925~6.425GHz -0.65 dBi @6425~6525GHz 0.98 dBi @6.525~6.875GHz 2.14 dBi @6.875~7.125GHz	0.71 dB @2.4G 1.18 dB @5G 1.31 dB @ 5.925~6.425GHz 1.31 dB @6425~6525GHz 1.31 dB @6.525~6.875GHz 1.31 dB @6.875~7.125GHz			285
28	INPAQ	Main	WA-P-LELE-04-036	1.63 dBi @ 2.4GHz 3.12 dBi @ 5GHz 3.18 dBi @ 5.925~6.425GHz 2.28 dBi @6425~6525GHz 3.57 dBi @6.525~6.875GHz 1.86 dBi @6.875~7.125GHz	0.79 dB @2.4G 1.39 dB @5G 1.39 dB @ 5.925~6.425GHz 1.39 dB @6425~6525GHz 1.39 dB @6.525~6.875GHz 1.39 dB @6.875~7.125GHz	PIFA	I-PEX MHF4-L	285
		Aux	WA-P-LELE-04-036	1.55 dBi @ 2.4GHz 3.31 dBi @ 5GHz 2.81 dBi @ 5.925~6.425GHz 1.01 dBi @6425~6525GHz 1.76 dBi @6.525~6.875GHz 2.7 dBi @6.875~7.125GHz	0.79 dB @2.4G 1.39 dB @5G 1.39 dB @ 5.925~6.425GHz 1.39 dB @6425~6525GHz 1.39 dB @6.525~6.875GHz 1.39 dB @6.875~7.125GHz			285

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
29	AWAN	Main	AYP6Y-100267	2.9 dBi @ 2.4GHz 3.7 dBi @ 5GHz 4.6 dBi @ 5.925~6.425GHz 3.9 dBi @ 6.425~6.525GHz 4.4 dBi @ 6.525~6.875GHz 4 dBi @ 6.875~7.125GHz	0.74 dB @ 2.4G 1.24dB @ 5G 1.41 dB @ 5.925~6.425GHz 1.41 dB @ 6.425~6.525GHz 1.41 dB @ 6.525~6.875GHz 1.41 dB @ 6.875~7.125GHz	PIFA	IPEX NGFF	249
		Aux	AYP6Y-100268	3 dBi @ 2.4GHz 2.5dBi @ 5GHz 1.5dBi @ 5GHz 3.4 dBi @ 5.925~6.425GHz 2.7 dBi @ 6.425~6.525GHz 3.2 dBi @ 6.525~6.875GHz 3.1 dBi @ 6.875~7.125GHz	1.45 dB @ 2.4G 2.44 dB @ 5G 2.76 dB @ 5.925~6.425GHz 2.76 dB @ 6.425~6.525GHz 2.76 dB @ 6.525~6.875GHz 2.76 dB @ 6.875~7.125GHz			485.2
30	ICT	Main	LA9RF358-CS-H	2.8 dBi @ 2.4GHz 3.6 dBi @ 5GHz 3.2dBi @ 5GHz 3.8 dBi @ 5.925~6.425GHz 3.8 dBi @ 6.425~6.525GHz 4 dBi @ 6.525~6.875GHz 3.8 dBi @ 6.875~7.125GHz	0.81 dB @ 2.4G 1.3 dB @ 5G 1.25 dB @ 5GHz 1.35 dB @ 5.925~6.425GHz 1.35 dB @ 6.425~6.525GHz 1.38 dB @ 6.525~6.875GHz 1.39 dB @ 6.875~7.125GHz	PIFA	I-PEX	249
		Aux	LA9RF359-CS-H	2.6 dBi @ 2.4GHz 2.2 dBi @ 5GHz 1.4 dBi @ 5GHz 2.3dBi @ 5.925~6.425GHz 2.2 dBi @ 6.425~6.525GHz 2.4 dBi @ 6.525~6.875GHz 2.4 dBi @ 6.875~7.125GHz	1.42 dB @ 2.4G 2.3dB @ 5G 2.28 dB @ 5GHz 2.34 dB @ 5.925~6.425GHz 2.38 dB @ 6.425~6.525GHz 2.44 dB @ 6.525~6.875GHz 2.44 dB @ 6.875~7.125GHz			485.2

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
31	Luxshare-ICT	Main	LA9RF453-CS-H	1.1dBi @ 2.4GHz 0.24dBi @ 5GHz -0.23dBi @ 5.925~6.425GHz -1.79dBi @6425~6525GHz -1.11dBi @6.525~6.875GHz -1.7 dBi @6.875~7.125GHz	1.57 dB @2.4G 2.40 dB @5G 2.47 dB @ 5.925~6.425GHz 2.54 dB @6425~6525GHz 2.56 dB @6.525~6.875GHz 2.57 dB @6.875~7.125GHz	PIFA	IPEX	640
		Aux	LA9RF454-CS-H	0.99dBi @ 2.4GHz 1.45 dBi @ 5GHz -0.06 dBi @ 5.925~6.425GHz -0.08 dBi @6425~6525GHz 0.7 dBi @6.525~6.875GHz 0.81 dBi @6.875~7.125GHz	0.78 dB @2.4G 1.19 dB @5G 1.24 dB @ 5.925~6.425GHz 1.27dB @6425~6525GHz 1.28 dB @6.525~6.875GHz 1.28 dB @6.875~7.125GHz			320
32	INPAQ	Main	WA-P-LE-02-116	2.46 dBi @ 2.4GHz 3.18 dBi @ 5GHz 3.48 dBi @ 5.925~6.425GHz 3.03 dBi @6425~6525GHz 3.92 dBi @6.525~6.875GHz 3.81 dBi @6.875~7.125GHz	1.44 dB @2.4G 2.21 dB @ 5GHz 2.36 dB @ 5.925~6.425GHz 2.41 dB @6425~6525GHz 2.46 dB @6.525~6.875GHz 2.54 dB @6.875~7.125GHz	PIFA	I-PEX MHF4-L	520
		Aux	WA-P-LE-01-023	1.38 dBi @ 2.4GHz 4.32 dBi @ 5GHz 3.7 dBi @ 5.925~6.425GHz 3.7 dBi @6425~6525GHz 3.49 dBi @6.525~6.875GHz 3.49 dBi @6.875~7.125GHz	0.67 dB @2.4G 1.01 dB @ 5GHz 1.10 dB @ 5.925~6.425GHz 1.12 dB @6425~6525GHz 1.15 dB @6.525~6.875GHz 1.19 dB @6.875~7.125GHz			243

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
33	Pulse	Main	TZ2416D	-0.57 dBi @ 2.4GHz 2.64 dBi @ 5GHz 1.46 dBi @ 5.925~6.425GHz 0.99 dBi @6425~6525GHz 0.99 dBi @6.525~6.875GHz 0.14 dBi @6.875~7.125GHz	1.51 dB @2.4G 2.35dB @ 5GHz 2.32 dB @ 5GHz 2.49 dB @ 5.925~6.425GHz 2.51 dB @6425~6525GHz 2.60 dB @6.525~6.875GHz 2.66 dB @6.875~7.125GHz	PIFA	I-PEX	520
		Aux	TZ2416E	0.73 dBi @ 2.4GHz 2.82 dBi @ 5.15~5.85GHz 2.41 dBi @ 5GHz 3.47 dBi @ 5.925~6.425GHz 2.81 dBi @6425~6525GHz 3.38 dBi @6.525~6.875GHz 3.38 dBi @6.875~7.125GHz	0.76 dB @2.4G 1.17 dB @ 5.15~5.85GHz 1.16 dB @ 5GHz 1.24 dB @ 5.925~6.425GHz 1.26 dB @6425~6525GHz 1.30 dB @6.525~6.875GHz 1.33 dB @6.875~7.125GHz			243
34	INPAQ	Main	WA-P-LE-02-065	2.88dBi @ 2.4GHz 4.75dBi @ 5GHz 4.24 dBi @ 5.925~6.425GHz 4.25 dBi @6425~6525GHz 4.39 dBi @6.525~6.875GHz 3.8 dBi @6.875~7.125GHz	0.72dB @ 2.4GHz 1.27dB @ 5GHz 1.27 dB @ 5.925~6.425GHz 1.27 dB @6425~6525GHz 1.27 dB @6.525~6.875GHz 1.27 dB @6.875~7.125GHz	PIFA	I-PEX MHF4-L	260
		Aux	WA-P-LE-01-007	2.93dBi @ 2.4GHz 4.3dBi @ 5GHz 4.06 dBi @ 5GHz 4.72 dBi @ 5.925~6.425GHz 4.12 dBi @6425~6525GHz 4.34 dBi @6.525~6.875GHz 3.89 dBi @6.875~7.125GHz	1.43dB @ 2.4GHz 2.51dB @ 5GHz 2.51dB @ 5.925~6.425GHz 2.51dB @6425~6525GHz 2.51dB @6.525~6.875GHz 2.51 dB @6.875~7.125GHz			510

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
35	PULSE	Main	TZ20941	2.79dBi @ 2.4GHz 4.59dBi @ 5GHz 3.42 dBi @ 5.925~6.425GHz 4.09 dBi @6425~6525GHz 4.24 dBi @6.525~6.875GHz 3.33 dBi @6.875~7.125GHz	0.78 dB @2.4G 1.09dB @ 5GHz 1.16 dB @ 5.925~6.425GHz 1.17 dB @6425~6525GHz 1.20 dB @6.525~6.875GHz 1.22 dB @6.875~7.125GHz	PIFA	I-PEX	260
		Aux	TZ20944	2.71dBi @ 2.4GHz 4.25dBi @ 5GHz 3.73 dBi @ 5GHz 4.65 dBi @ 5.925~6.425GHz 3.85 dBi @6425~6525GHz 4.21 dBi @6.525~6.875GHz 3.81 dBi @6.875~7.125GHz	1.55 dB @2.4G 2.18dB @ 5GHz 2.17 dB @ 5GHz 2.3 dB @ 5.925~6.425GHz 2.31 dB @6425~6525GHz 2.38 dB @6.525~6.875GHz 2.41 dB @6.875~7.125GHz			510
36	Luxshare-ICT	Main	LA9RF0 59-CS-H	0.30 dBi@ 2.4 GHz 0.20 dBi@5.15~5.895 GHz 1.20 dBi@ 5.925~6.425 GHz 0.90 dB@ 6.425~6.525 GHz 0.90 dBi@6.525~6.875 GHz -1.80 dBi@ 6.875G~7.125 GHz	1.84 dB@ 2.4 GHz 2.92 dB@5.15~5.895 GHz 3.52 dB@ 5.925~6.425 GHz 3.96 dB@ 6.425~6.525 GHz 3.96 dB@ 6.525~6.875 GHz 4.21 dB@6.875G~7.125 GHz	Dipole	SMA R/P(RF Cable : IPEX, ICT, CNC SMA Jack 0 81 BK 42	925 (RF Cable: 42)
		Aux	LA9RF0 59-CS-H	-1.10 dBi@ 2.4 GHz -1.10 dBi@ 5 GHz -2.8 dBi @ 5GHz 1.40 dBi@ 5.925~6.425 GHz 1.40 dBi@ 6.425~6.525 GHz -0.30 dBi@ 6.525~6.875 GHz -1.60 dBi@6.875G~7.125 GHz	1.75 dB@2.4 GHz 2.78 dB@5 GHz 2.7 dB @ 5GHz 3.36 dB@ 5.925~6.425 GHz 3.36 dB@ 6.425~6.525 GHz 3.72 dB@ 6.525~6.875 GHz 3.72 dB@6.875G~7.125 GHz			876 (RF Cable: 42)



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
37	INPAQ	Main	DAM-I3-H1-M2-800-10-66	1.38dBi @ 2.4GHz 3.64dBi @ 5GHz 2.77 dBi @ 5GHz 2.8 dBi @ 5.925~6.425GHz 0.9 dBi @6425~6525GHz 1.11 dBi @6.525~6.875GHz 2.7 dBi @6.875~7.125GHz	2.0dB @2.4GHz 3.0dB @ 5GHz 3.44 dB @ 5.925~6.425GHz 3.51 dB @6425~6525GHz 3.59 dB @6.525~6.875GHz 3.70 dB @6.875~7.125GHz	Dipole	SMA RP(RF Cable : IPEX, ICT, CNC SMA Jack 0 81 BK 42	800 (RF Cable: 42)
		Aux	DAM-I3-H1-M2-800-10-66	2.27dBi @ 2.4GHz 3.53dBi @ 5.GHz 3.46 dBi @ 5GHz 1.47 dBi @ 5.925~6.425GHz 1.54 dBi @6425~6525GHz 2.45 dBi @6.525~6.875GHz 3.08 dBi @6.875~7.125GHz	2.0 dB @2.4GHz 3.0 dB @ 5GHz 3.44 dB @ 5.925~6.425GHz 3.51 dB @6425~6525GHz 3.59 dB @6.525~6.875GHz 3.70 dB @6.875~7.125GHz			800 (RF Cable: 42)
38	LUXSH ARE-ICT	Main	LA9RF442-CS-H	2.49 dBi @ 2.4GHz 4.49dBi @ 5GHz 4.53dBi @ 5.925~6.425GHz 3.9 dBi @6425~6525GHz 3.56 dBi @6.525~6.875GHz 3.03 dBi @6.875~7.125GHz	1.72 dB @2.4G 2.71 dB @5G 2.8 dB @ 5.925~6.425GHz 3.9 dB @6425~6525GHz 2.91 dB @6.525~6.875GHz 2.97 dB @6.875~7.125GHz	PIFA	I PEX	573
		Aux	LA9RF443-CS-H	2.78 dBi @ 2.4GHz 4.58 dBi @ 5GHz 4.69 dBi @ 5.925~6.425GHz 3.73 dBi @6425~6525GHz 4.17 dBi @6.525~6.875GHz 3.51 dBi @6.875~7.125GHz	0.79 dB @2.4G 1.27 dB @5G 1.31 dB @ 5.925~6.425GHz 1.33 dB @6425~6525GHz 1.35 dB @6.525~6.875GHz 1.36 dB @6.875~7.125GHz			265



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
39	INPAQ	Main	WA-P-LE-02-122	2.05 dBi @ 2.4GHz 4.38 dBi @ 5GHz 4.19 dBi @ 5.925~6.425GHz 3.80 dBi @6425~6525GHz 3.38 dBi @6.525~6.875GHz 2.98 dBi @6.875~7.125GHz	1.63 dB @2.4G 2.86 dB @5G 2.86 dB @ 5.925~6.425GHz 2.86 dB @6425~6525GHz 2.86 dB @6.525~6.875GHz 2.86 dB @6.875~7.125GHz	PIFA	I-PEX MHF4-L	573
		Aux	WA-P-LE-01-028	2.7 dBi @ 2.4GHz 4.1 dBi @ 5GHz 4.34 dBi @ 5.925~6.425GHz 3.51 dBi @6425~6525GHz 3.68 dBi @6.525~6.875GHz 3.21 dBi @6.875~7.125GHz	0.77 dB @2.4G 1.36 dB @5G 1.36 dB @ 5.925~6.425GHz 1.36 dB @6425~6525GHz 1.36 dB @6.525~6.875GHz 1.36 dB @6.875~7.125GHz			265
40	Pulse	Main	DC33002KJ00 (SZ18994)	0.38dBi @ 2.4GHz 2.91dBi @ 5GHz 2.77dBi @ 5.925~6.425GHz 2.79dBi @6425~6525GHz 2.79dBi @6.525~6.875GHz 1.13dBi @6.875~7.125GHz	1.24dB @2.4G 1.84dB @5G 2.06dB @ 5.925~6.425GHz 2.09dB @6425~6525GHz 2.16dB @6.525~6.875GHz 2.24dB @6.875~7.125GHz	PIFA	IPEX 20565-001R-13	374
		Aux	DC33002KJ10 (SZ18991)	2.88dBi @ 2.4GHz 2.64dBi @ 5GHz 2.12dBi @ 5.925~6.425GHz 0.48dBi @6425~6525GHz 0.89dBi @6.525~6.875GHz 0.93dBi @6.875~7.125GHz	0.99dB @2.4G 1.55dB @5G 1.66dB @ 5.925~6.425GHz 1.68dB @6425~6525GHz 1.73dB @6.525~6.875GHz 1.8dB @6.875~7.125GHz			300

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
41	High-Tek Electronics Co., Ltd	Main	DC33002KI00 (0ACCN020027N)	2.61dBi @ 2.4GHz 2.98dBi @ 5GHz 2.78dBi @ 5.925~6.425GHz 2.83dBi @6425~6525GHz 2.81dBi @6.525~6.875GHz 2.57dBi @6.875~7.125GHz	1.5dB @2.4G 2.19dB @5G 2.5dB @ 5.925~6.425GHz 2.53dB @6425~6525GHz 2.6dB @6.525~6.875GHz 2.73dB @6.875~7.125GHz	PIFA	I-PEX	400
		Aux	DC33002KI10 (0ACCN020028N)	2.93dBi @ 2.4GHz 2.95dBi @ 5GHz 2.67 dBi @ 5GHz 2.48dBi @ 5.925~6.425GHz 1.23dBi @6425~6525GHz 2.52dBi @6.525~6.875GHz 2.52dBi @6.875~7.125GHz	1.27dB @2.4G 1.97dB @5G 1.91 dB @ 5GHz 2.13dB @ 5.925~6.425GHz 2.15dB @6425~6525GHz 2.21dB @6.525~6.875GHz 2.32dB @6.875~7.125GHz			340
42	Pulse	Main	DQ602487W00	1.06 dBi @ 2.4GHz 0.84 dBi @ 5GHz -0.15 dBi @ 5.925~6.425GHz -1.5 dBi @6425~6525GHz -0.64 dBi @6.525~6.875GHz -1.93 dBi @6.875~7.125GHz	0.52 dB @2.4G 0.80 dB @5G 0.78 dB @ 5GHz 0.84 dB @ 5.925~6.425GHz 0.85 dB @6425~6525GHz 0.87 dB @6.525~6.875GHz 0.91 dB @6.875~7.125GHz	PIFA	I-PEX	142
		Aux	DQ602487W00	2.49 dBi @ 2.4GHz 0.74 dBi @ 5GHz -0.43 dBi @ 5.925~6.425GHz -0.84 dBi @6425~6525GHz 0.01 dBi @6.525~6.875GHz -0.65 dBi @6.875~7.125GHz	1.13 dB @2.4G 1.71 dB @5G 1.85 dB @ 5.925~6.425GHz 1.9 dB @6425~6525GHz 1.95 dB @6.525~6.875GHz 2.01 dB @6.875~7.125GHz			314

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
43	ICT	-	DQ64AT03400	2.41 dBi @ 2.4GHz 2.72 dBi @ 5GHz 3.78 dBi @ 5.925~6.425GHz 3.91 dBi @ 6.425~6.875GHz 3.91 dBi @ 6.525~6.875GHz 3.26 dBi @ 6.875~7.125GHz	0.45 dB @ 2.4G 0.70 dB @ 5G 0.84 dB @ 5.925~6.425GHz 0.84 dB @ 6.425~6.875GHz 0.84 dB @ 6.525~6.875GHz 0.84 dB @ 6.875~7.125GHz	PIFA	I-PEX	145
		Aux	DQ64AT03400	1.32 dBi @ 2.4GHz 2.98 dBi @ 5GHz 2.68 dBi @ 5.925~6.425GHz 3.04 dBi @ 6.425~6.875GHz 3.04 dBi @ 6.525~6.875GHz 1.87 dBi @ 6.875~7.125GHz	1.07 dB @ 2.4G 1.66 dB @ 5G 1.99 dB @ 5.925~6.425GHz 1.99 dB @ 6.425~6.875GHz 1.99 dB @ 6.525~6.875GHz 1.99 dB @ 6.875~7.125GHz			317
44	Pulse	Main	DQ602488W00	1.23 dBi @ 2.4GHz 3.31 dBi @ 5GHz 3.86 dBi @ 5.925~6.425GHz 3.78 dBi @ 6.425~6.875GHz 3.78 dBi @ 6.525~6.875GHz 2.64 dBi @ 6.875~7.125GHz	0.56 dB @ 2.4G 0.88 dB @ 5G 0.90 dB @ 5.925~6.425GHz 0.93 dB @ 6.425~6.875GHz 0.95 dB @ 6.525~6.875GHz 1.01 dB @ 6.875~7.125GHz	PIFA	I-PEX	154
		Aux	DQ602488W00	2.68 dBi @ 2.4GHz 2.57 dBi @ 5GHz 2.44 dBi @ 5.925~6.425GHz 2.23 dBi @ 6.425~6.875GHz 1.68 dBi @ 6.525~6.875GHz 1.91 dBi @ 6.875~7.125GHz	1.4 dB @ 2.4G 2.09 dB @ 5G 2.23 dB @ 5.925~6.425GHz 2.32 dB @ 6.425~6.875GHz 2.42 dB @ 6.525~6.875GHz 2.46 dB @ 6.875~7.125GHz			386

Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
45	ICT	Main	DQ64AT03500	2.61 dBi @ 2.4GHz 3.36 dBi @ 5GHz 3.03 dBi @ 5GHz 3.88 dBi @ 5.925~6.425GHz 3.83 dBi @ 6425~6525GHz 3.7 dBi @ 6.525~6.875GHz 3.06 dBi @ 6.875~7.125GHz	0.47 dB @ 2.4G 0.74 dB @ 5G 0.90 dB @ 5.925~6.425GHz 0.90 dB @ 6425~6525GHz 0.90 dB @ 6.525~6.875GHz 0.90 dB @ 6.875~7.125GHz	PIFA	i-pec(MHF)	154
		Aux	DQ64AT03500	2.81 dBi @ 2.4GHz 3.82 dBi @ 5GHz 3.63 dBi @ 5.925~6.425GHz 3 dBi @ 6425~6525GHz 2.86 dBi @ 6.525~6.875GHz 2.86 dBi @ 6.875~7.125GHz	1.23 dB @ 2.4G 1.91 dB @ 5G 2.29 dB @ 5.925~6.425GHz 2.29 dB @ 6425~6525GHz 2.29 dB @ 6.525~6.875GHz 2.29 dB @ 6.875~7.125GHz			386

# Newly

Antenna Set No.	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
46	LUXSHAREICT	Main	LA9RF467-CS-H	0.18 dBi @ 2.4GHz 4.3 dBi @ 5GHz 4.24 dBi @ 5.925~6.425GHz 4.04 dBi @ 6.425~6.525GHz 4.28 dBi @ 6.525~6.875GHz 3.98 dBi @ 6.875~7.125GHz	0.11 dB @ 2.4GHz 0.17 dB @ 5GHz 0.17 dB @ 5.925~6.425GHz 0.18 dB @ 6.425~6.525GHz 0.18 dB @ 6.525~6.875GHz 0.18 dB @ 6.875~7.125GHz	PIFA	IPEX	45
		Aux	LA9RF468-CS-H	-0.23dBi @ 2.4GHz 4.46dBi @ 5GHz 4.15 dBi @ 5.925~6.425GHz 3.32 dBi @ 6.425~6.525GHz 3.32 dBi @ 6.525~6.875GHz 2.46 dBi @ 6.875~7.125GHz	1.08 dB @ 2.4GHz 1.72 dB @ 5GHz 1.74 dB @ 5.925~6.425GHz 1.79 dB @ 6.425~6.525GHz 1.79 dB @ 6.525~6.875GHz 1.81 dB @ 6.875~7.125GHz			450
47	INPAQ	Main	MDA-LE-02-017	-0.31 dBi @ 2.4GHz 3.37 dBi @ 5GHz 4.12 dBi @ 5.925~6.425GHz 3.93 dBi @ 6.425~6.525GHz 3.87 dBi @ 6.525~6.875GHz 3.87 dBi @ 6.875~7.125GHz	0.34 dB @ 2.4GHz 0.59 dB @ 5GHz 0.59 dB @ 5.925~6.425GHz 0.6 dB @ 6.425~6.525GHz 0.6 dB @ 6.525~6.875GHz 0.6 dB @ 6.875~7.125GHz	PIFA	I-PEX MHF-4L	45
		Aux	MDA-LE-01-008	-0.44 dBi @ 2.4GHz 3.51 dBi @ 5GHz 4.09 dBi @ 5.925~6.425GHz 2.9 dBi @ 6.425~6.525GHz 2.9 dBi @ 6.525~6.875GHz 2.44 dBi @ 6.875~7.125GHz	1.08 dB @ 2.4GHz 1.66 dB @ 5GHz 1.66 dB @ 5.925~6.425GHz 1.67 dB @ 6.425~6.525GHz 1.67 dB @ 6.525~6.875GHz 1.67 dB @ 6.875~7.125GHz			450



Antenna Set No.	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
48	Galtronics	Main	02112610-07678 (DC33002P500)	1.8dBi @ 2.4GHz 2.36dBi @ 5GHz	1.45 dB @2.4GHz 2.37dB @5GHz	PIFA	I-PEX	474
		Aux	02112610-07679 (DC33002P510)	2.84dBi @ 2.4GHz 1.34dBi @ 5GHz	2.31dB @2.4GHz 3.78dB @5GHz			748
49	WNC	Main	DC33002HZ00 (81EABA15.GCN)	1.92dBi @ 2.4GHz 2.25dBi @ 5GHz	1.98 dB @2.4GHz 2.88dB @5GHz	PIFA	I-pex MHF4L	480
		Aux	DC33002HZ10 (81EABA15.GCP)	1.62dBi @ 2.4GHz 1.51dBi @ 5GHz	1.45dB @2.4GHz 2.24dB @5GHz			746
50	WNC	Main	DC33002I000 (81EABA15.GCL)	1.52dBi @ 2.4GHz 2.23dBi @ 5GHz	1.77 dB @2.4GHz 2.77dB @5GHz	PIFA	I-pex MHF4L	583.5
		Aux	DC33002I010 (81EABA15.GCM)	2.63dBi @ 2.4GHz 0.43dBi @ 5GHz	2.17dB @2.4GHz 3.06dB @5GHz			824



Antenna Set No	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
51	High-tek	Main	DC33002U900 (0ACCN022033N)	2.8dBi @ 2.4GHz 2.39dBi @ 5GHz 3.52dBi @ 5.925~6.425GHz 2.22dBi @6425~6525GHz 2.17dBi @6.525~6.875GHz 2.96dBi @6.875~7.125GHz	1.53dB @2.4GHz 2.33dB @5GHz 2.5dB @ 5.925~6.425GHz 2.6dB @6425~6525GHz 2.7dB @6.525~6.875GHz 2.8dB @6.875~7.125GHz	PIFA	IPX MHF4	475
		Aux	DC33002U910 (0ACCN022034N)	2.6dBi @ 2.4GHz 2.81dBi @ 5GHz 3.71dBi @ 5.925~6.425GHz 2.07dBi @6425~6525GHz 2.16dBi @6.525~6.875GHz 2.17dBi @6.875~7.125GHz	1.25dB @2.4GHz 1.91dB @5GHz 2.1dB @ 5.925~6.425GHz 2.1dB @6425~6525GHz 2.2dB @6.525~6.875GHz 2.3dB @6.875~7.125GHz			395
52	Pulse	Main	DC33002U800 (TZ2558D)	2.58dBi @ 2.4GHz 2.21dBi @ 5GHz 3.02dBi @ 5.925~6.425GHz 1.61dBi @6425~6525GHz 2.06dBi @6.525~6.875GHz 2.66dBi @6.875~7.125GHz	1.53dB @2.4GHz 2.33dB @5GHz 2.5dB @ 5.925~6.425GHz 2.6dB @6425~6525GHz 2.7dB @6.525~6.875GHz 2.8dB @6.875~7.125GHz	PIFA	IPX MHF4	475
		Aux	DC33002U810 (TZ2558E)	2.4dBi @ 2.4GHz 2.75dBi @ 5GHz 2.58dBi @ 5.925~6.425GHz 1.66dBi @6425~6525GHz 1.85dBi @6.525~6.875GHz 1.93dBi @6.875~7.125GHz	1.25dB @2.4GHz 1.96dB @5GHz 2.1dB @ 5.925~6.425GHz 2.1dB @6425~6525GHz 2.2dB @6.525~6.875GHz 2.3dB @6.875~7.125GHz			395

Antenna Set No.	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
53	High-tek	Main	DC33002UA00 (0ACCN022037N)	2.63dBi @ 2.4GHz 2.33dBi @ 5GHz 1.87dBi @ 5.925~6.425GHz 2.58dBi @6425~6525GHz 1.92dBi @6.525~6.875GHz 2.26dBi @6.875~7.125GHz	2.35dB @2.4GHz 3.63dB @5GHz 3.9dB @ 5.925~6.425GHz 4dB @6425~6525GHz 4.1dB @6.525~6.875GHz 4.2dB @6.875~7.125GHz	PIFA	IPX MHF4	741
		Aux	DC33002UA10 (0ACCN022038N)	2.01dBi @ 2.4GHz 2.79dBi @ 5GHz 2.52dBi @ 5.925~6.425GHz 2.41dBi @6425~6525GHz 1.91dBi @6.525~6.875GHz 2.31dBi @6.875~7.125GHz	0.49dB @2.4GHz 0.77dB @5GHz 0.82dB @ 5.925~6.425GHz 0.82dB @6425~6525GHz 0.9dB @6.525~6.875GHz 0.9dB @6.875~7.125GHz			155
54	South-star	Main	DC33002UG00 (3.N201.0242)	2.34dBi @ 2.4GHz 2.04dBi @ 5GHz 1.76dBi @ 5.925~6.425GHz 2.34dBi @6425~6525GHz 1.72dBi @6.525~6.875GHz 1.89dBi @6.875~7.125GHz	2.35dB @2.4GHz 3.63dB @5GHz 3.9dB @ 5.925~6.425GHz 4dB @6425~6525GHz 4.1dB @6.525~6.875GHz 4.2dB @6.875~7.125GHz	PIFA	IPX MHF4	741
		Aux	DC33002UG10 (3.N201.0243)	1.78dBi @ 2.4GHz 2.52dBi @ 5GHz 2.43dBi @ 5.925~6.425GHz 2.23dBi @6425~6525GHz 1.72dBi @6.525~6.875GHz 2.12dBi @6.875~7.125GHz	0.49dB @2.4GHz 0.77dB @5GHz 0.82dB @ 5.925~6.425GHz 0.82dB @6425~6525GHz 0.9dB @6.525~6.875GHz 0.9dB @6.875~7.125GHz			155

Antenna Set No.	Brand	Main/Aux	Model	Peak gain with cable loss	Cable Loss (dB)	Antenna Type	Connector Type	Cable Length (mm)
55	High-tek	Main	DC33002UE00 (0ACCN023001N)	1.91dBi @ 2.4GHz 2.86dBi @ 5GHz 2.96dBi @ 5.925~6.425GHz 1.37dBi @6425~6525GHz 1.22dBi @6.525~6.875GHz 2.05dBi @6.875~7.125GHz	1.33dB @2.4GHz 2.08dB @5GHz 2.2dB @ 5.925~6.425GHz 2.27dB @6425~6525GHz 2.32dB @6.525~6.875GHz 2.38dB @6.875~7.125GHz	PIFA	IPX MHF4	420
		Aux	DC33002UE10 (0ACCN023002N)	0.76dBi @ 2.4GHz 2.97dBi @ 5GHz 2.22dBi @ 5.925~6.425GHz 2.59dBi @6425~6525GHz 2.11dBi @6.525~6.875GHz 2.2dBi @6.875~7.125GHz	2.37dB @2.4GHz 3.72dB @5GHz 3.92dB @ 5.925~6.425GHz 4.06dB @6425~6525GHz 4.14dB @6.525~6.875GHz 4.25dB @6.875~7.125GHz			750
56	South-star	Main	DC33002UH00 (3.N201.0244)	1.83dBi @ 2.4GHz 2.37dBi @ 5GHz 2.74dBi @ 5.925~6.425GHz 1.17dBi @6425~6525GHz 1.1dBi @6.525~6.875GHz 1.86dBi @6.875~7.125GHz	1.33dB @2.4GHz 2.06dB @5GHz 2.2dB @ 5.925~6.425GHz 2.27dB @6425~6525GHz 2.32dB @6.525~6.875GHz 2.38dB @6.875~7.125GHz	PIFA	IPX MHF4	420
		Aux	DC33002UH10 (3.N201.0245)	0.54dBi @ 2.4GHz 2.81dBi @ 5GHz 2.13dBi @ 5.925~6.425GHz 2.34dBi @6425~6525GHz 2.06dBi @6.525~6.875GHz 2.12dBi @6.875~7.125GHz	2.37dB @2.4GHz 3.72dB @5GHz 3.92dB @ 5.925~6.425GHz 4.06dB @6425~6525GHz 4.14dB @6.525~6.875GHz 4.25dB @6.875~7.125GHz			750

3. Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

## Appendix - Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any coents, please feel free to contact us at the following:

### Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

### Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

### Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

Web Site: [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---