

Radio Test Report

Report No.: RJBEBU-WTW-P21120159-1 R1

Test Model: RGP0127

Received Date: 2021/12/28

Test Date: 2022/1/5

Issued Date: 2022/1/17

Applicant: Corsair Memory, Inc.

Address: 115 North McCarthy Blvd, Milpitas, CA 95035, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results	5
2.1 Test Instruments	6
2.2 Measurement Uncertainty	6
2.3 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	8
3.3 Test Conditions	9
3.4 Assembly	9
3.5 Antenna Specifications	10
3.5.1 Antenna Gain	10
3.5.2 Antenna Pattern	10
4 Test Results	12
4.1 Frequency Tolerance Measurement	12
4.1.1 Limits of Frequency Tolerance Measurement	12
4.1.2 Test Setup	12
4.1.3 Test Results	12
4.2 Occupied Bandwidth Measurement (99% power bandwidth)	13
4.2.1 Limits of Occupied Bandwidth Measurement	13
4.2.2 Test Setup	13
4.2.3 Test Results	13
4.3 Spurious Emissions for Transmitter Measurement	17
4.3.1 Limits of Spurious Emissions	17
4.3.2 Test Setup	17
4.3.3 Test Results	18
4.4 Antenna Power Measurement	29
4.4.1 Limits of Antenna Power	29
4.4.2 Test Setup	29
4.4.3 Test Results	30
4.5 Spurious Emissions for Receiver	31
4.5.1 Limits of Spurious Emissions for Receiver	31
4.5.2 Test Setup	31
4.5.3 Test Result	32
4.6 Interference Prevention Function	36
4.6.1 Limits of Interference Prevention Function	36
4.6.2 Test Setup	36
4.6.3 Test Results	36
5 Photographs of the Test Configuration	37
Appendix - Information of the Testing Laboratories	38

Release Control Record

Issue No.	Description	Date Issued
RJBEBU-WTW-P21120159-1	Original release.	2022/1/14
RJBEBU-WTW-P21120159-1 R1	Modify the Manufacturer of battery in section 3.1.	2022/1/17

1 Certificate of Conformity

Product: Wireless keyboard

Brand: CORSAIR

Test Model: RGP0127

Sample Status: Engineering sample

Applicant: Corsair Memory, Inc.

Test Date: 2022/1/5

Standards: ARIB STD-T66 (V3.7), MIC notice 88 Appendix 43
Certification Ordinance Article 2-1-19

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Annie Chang

Date: 2022/1/17

Annie Chang / Senior Specialist

Approved by :

Jeremy Lin

Date: 2022/1/17

Jeremy Lin / Project Engineer

2 Summary of Test Results

The EUT has been tested according to the following specifications:

Notice 88 Appendix 43 Reference	ARIB STD- T66 Ref.	Report Reference	Parameter	Test Results (Note)
General Provisions				
C	3.2 (4)	4.1	Frequency tolerance	C
D	3.2 (7)	4.2	Occupied bandwidth	C
E	3.2 (6)	4.4	Spurious emissions	C
Transmitting Equipment				
F	3.2 (2)	4.4	Antenna power	C
--	--	--	SAR	NA
Transmitting Antenna				
--	--	3.5	Type, configuration, etc. of transmitting antenna	C
--	--	3.5	Direction pattern of transmitting antenna	C
Receiving Equipment				
G	3.3 (1)	4.5	Spurious emissions of receiver	C
--	--	3.5	Refer to all articles for transmitting antenna	C
Operating Frequency 2400 to 2483.5MHz				
--	3.7 (1)	3.4	High Frequency/modulation section cannot be opened easily	C
--	3.1 (1)	3.1	Communication method	C
--	3.2 (1)a	3.1	Modulation method	C
--	3.2 (1)a	3.1	Spread spectrum method	NA
--	3.2 (2)	4.4	Antenna power	C
--	3.6 (2)	4.4	Absolute gain of transmitting antenna	C
--	3.6 (2)	4.4	Angular width of principal radiation (AWPR)	NA
--	3.2 (10)	--	Number of carriers within 1 MHz bandwidth in OFDM	NA
--	3.2 (8)	--	Diffusion bandwidth	NA
--	3.2 (9)	--	Spreading factor	NA
--	3.2 (11)	--	Frequency retention time (FH employed)	NA
--	3.4.1(1)	4.6	Interference Prevention Function	C
--	3.4.1(3)	--	Carrier Sense Capability	NA

Note:

1. C = Conform NC = Not Conform NT = Not Tested NA = Not Applicable
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until	Calibration Authority	Cal. Method
MIMO Power measurement Test set (4X4) KEYSIGHT	U2021XA	U2021XA_001	2021/6/16	2022/6/15	ETC	c)
Spectrum Analyzer R&S	FSV40	101042	2021/9/9	2022/9/8	ETC	c)
Spectrum Analyzer KEYSIGHT	N9030A	MY54490260	2021/7/23	2022/7/22	ETC	c)
Pulse Power Sensor Anritsu	MA2411B	0738404	2021/4/15	2022/4/14	ETC	c)
Peak Power meter Anritsu	ML2495A	0842014	2021/4/15	2022/4/14	ETC	c)
MXG Vector Signal Generator KEYSIGHT	N5182B	MY53052658	2021/5/19	2022/5/18	ETC	c)
True RMS Clamp Meter Fluke	325	31130711WS	2021/6/2	2022/6/1	ETC	c)
AC POWER SOURCE Schaffner	Proflin2105-208NSG1007	55616	2021/6/2	2022/6/1	ETC	c)

NOTE: Calibration Method

- a) : Calibration conducted by the National Institute of Information and Communications Technology(NICT) or a designated calibration agency under Article 102-18 paragraph (1) of the Radio Law.
- b) : Calibration conducted pursuant to the provisions of Article 135 or Article 144 of the Measurement Law (Law No. 51 of 1992) Japan Calibration Service System.
- c) : Calibration conducted in foreign countries, which shall be equivalent to the calibration conducted by the NICT or a designated calibration agency under Article 102-18 paragraph (1).
- d) : Calibration conducted by using other equipment that listed above from a) to c)

2.2 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in TR 100 028-1.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameter	Uncertainty
Occupied Bandwidth	206.50 Hz
Spurious emissions	3.93 dB
Output power density	1.11 dB
Out of band radiated power	3.93 dB
Frequency Tolerance	603.76 Hz

2.3 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Wireless keyboard
Brand	CORSAIR
Test Model	RGP0127
Status of EUT	Engineering sample
Nominal Voltage	3.7Vdc from battery or 5Vdc from host equipment
Modulation Type	GFSK
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Rated RF Output Power	1mW
Conducted RF Output Power	0.918mW
Radiated RF Output Power	0.289mW
Antenna Type	METAL antenna with -5.02dBi gain
Antenna Connector	N/A
Accessory Device	N/A
Data Cable Supplied	Shielded USB Type C – Type A Cable (1.8m)

Note:

1. Bluetooth & GFSK technologies can not transmit at same time.

2. The EUT uses following rechargeable battery.

Manufacturer	Hangzhou Future Power Technology Co., Ltd.
Model	FT5936E2P
Rating	3.7Vdc

3. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Note: The channels which were indicated in bold type of the above channel list were selected as representative test channel. Therefore only the data of the test channels were recorded in this report.

By means of test software provided by manufacture, the power levels during the tests were set according to the following codes:

Channel	Power setting
0	0
39	0
78	0

3.3 Test Conditions

Test Conditions		Voltage (Vdc)
V_{normal}	-	5
$V_{max.}$	+10%	5.5
$V_{min.}$	-10%	4.5

Test modes are presented in the report as below:

Test Item	Environmental Conditions
Frequency Tolerance	25 deg.C, 76% RH
Occupied Bandwidth	25 deg.C, 76% RH
Spurious Emissions for Transmitter	25 deg.C, 76% RH
Antenna Power	25 deg.C, 76% RH
Spurious Emissions for Receiver	25 deg.C, 76% RH
Interference Prevention Function	25 deg.C, 76% RH

3.4 Assembly


The EUT used a kind of particular screw, which could not operated by a tool bought in the market. Only means of brute force will be able to open.

3.5 Antenna Specifications


3.5.1 Antenna Gain

Antenna Type	Max. Gain (dBi)
METAL antenna	-5.02


3.5.2 Antenna Pattern




Frequency (MHz) : 2402.00 Antenna Polarity : Horizontal Average Value (dBi) : -12.42
 Maximum Value (dBi) : -8.46 Maximum Value (degree) : 36
 Minimum Value (dBi) : -27.73 Minimum Value (degree) : 191




Frequency (MHz) : 2402.00 Antenna Polarity : Vertical Average Value (dBi) : -9.80
 Maximum Value (dBi) : -5.02 Maximum Value (degree) : 162
 Minimum Value (dBi) : -25.37 Minimum Value (degree) : 264




Frequency (MHz) : 2441.00 Antenna Polarity : Horizontal Average Value (dBi) : -12.02
 Maximum Value (dBi) : -7.74 Maximum Value (degree) : 97
 Minimum Value (dBi) : -24.64 Minimum Value (degree) : 336



Frequency (MHz) : 2441.00 Antenna Polarity : Vertical Average Value (dBi) : -10.21
 Maximum Value (dBi) : -5.08 Maximum Value (degree) : 166
 Minimum Value (dBi) : -21.52 Minimum Value (degree) : 248



Frequency (MHz) : 2480.00 Antenna Polarity : Horizontal Average Value (dBi) : -11.02
 Maximum Value (dBi) : -5.70 Maximum Value (degree) : 264
 Minimum Value (dBi) : -27.84 Minimum Value (degree) : 185



Frequency (MHz) : 2480.00 Antenna Polarity : Vertical Average Value (dBi) : -10.07
 Maximum Value (dBi) : -5.43 Maximum Value (degree) : 204
 Minimum Value (dBi) : -20.79 Minimum Value (degree) : 1


4 Test Results

4.1 Frequency Tolerance Measurement

4.1.1 Limits of Frequency Tolerance Measurement

Tolerance of frequency shall be +/- 50ppm

4.1.2 Test Setup



4.1.3 Test Results

Channel	Frequency (MHz)	V_{normal}		$V_{max.}$		$V_{min.}$	
		Carrier frequency (MHz)	Frequency tolerance (ppm)	Carrier frequency (MHz)	Frequency tolerance (ppm)	Carrier frequency (MHz)	Frequency tolerance (ppm)
0	2402	2402.000160	0.066	2402.000119	0.049	2402.000039	0.016
39	2441	2440.999999	-0.000	2441.000040	0.016	2441.000040	0.016
78	2480	2480.000000	0.000	2479.999960	-0.016	2480.000000	0.000

4.2 Occupied Bandwidth Measurement (99% power bandwidth)

4.2.1 Limits of Occupied Bandwidth Measurement

Item	Limit
Occupied bandwidth	<26MHz

4.2.2 Test Setup




4.2.3 Test Results


Channel	Frequency (MHz)	V_{normal}	$V_{max.}$	$V_{min.}$
		Occupied bandwidth (MHz)	Occupied bandwidth (MHz)	Occupied bandwidth (MHz)
0	2402	2.02	2.02	2.01
39	2441	2.02	2.02	2.02
78	2480	2.02	2.02	2.02

NOTE: For the test plots please refer to the below pages.


V_{normal}



V_{max.}




V_{min.}




CH 0 (2402MHz)


V_{normal}



V_{max.}




V_{min.}




CH 39 (2441MHz)


V_{normal}



V_{max.}



V_{min.}



CH 78 (2480MHz)

4.3 Spurious Emissions for Transmitter Measurement

4.3.1 Limits of Spurious Emissions

Frequencies (MHz)	Limit
Operating frequency 2400 to 2483.5MHz	
30.0MHz to 1000.0MHz	$\leq 0.25 \text{ uW/100kHz}$
1000.0MHz to 2387MHz	$\leq 2.5 \text{ uW/MHz}$
2387.0MHz to 2400.0MHz	$\leq 25 \text{ uW/MHz}$
2483.5MHz to 2496.5MHz	$\leq 25 \text{ uW/MHz}$
2496.5MHz to 12500.0MHz	$\leq 2.5 \text{ uW/MHz}$

4.3.2 Test Setup




4.3.3 Test Results

TEST CHANNEL		CH 0 (2402MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASURE. VALUE(μ W)	LIMIT (μ W)	RESULT
V_{normal}	30MHz to 1000MHz	980.478	0.000094	0.25	PASS
	1000MHz to 2387MHz	2386.133	0.008570	2.5	PASS
	2387MHz to 2400MHz	2399.998	2.328091	25	PASS
	2483.5MHz to 2496.5MHz	2492.364	0.017660	25	PASS
	2496.5MHz to 12500MHz	11323.338	0.018578	2.5	PASS
V_{max.}	30MHz to 1000MHz	797.391	0.000120	0.25	PASS
	1000MHz to 2387MHz	2376.250	0.005333	2.5	PASS
	2387MHz to 2400MHz	2399.990	2.344229	25	PASS
	2483.5MHz to 2496.5MHz	2492.292	0.016293	25	PASS
	2496.5MHz to 12500MHz	12376.206	0.025351	2.5	PASS
V_{min.}	30MHz to 1000MHz	907.971	0.000092	0.25	PASS
	1000MHz to 2387MHz	1876.237	0.007096	2.5	PASS
	2387MHz to 2400MHz	2399.995	2.259436	25	PASS
	2483.5MHz to 2496.5MHz	2492.887	0.016596	25	PASS
	2496.5MHz to 12500MHz	11868.529	0.018621	2.5	PASS
TEST CHANNEL		CH 39 (2441MHz)			
V_{normal}	30MHz to 1000MHz	721.852	0.000167	0.25	PASS
	1000MHz to 2387MHz	2376.770	0.005768	2.5	PASS
	2387MHz to 2400MHz	2393.716	0.013122	25	PASS
	2483.5MHz to 2496.5MHz	2489.416	0.010069	25	PASS
	2496.5MHz to 12500MHz	11926.049	0.019498	2.5	PASS
V_{max.}	30MHz to 1000MHz	738.706	0.000097	0.25	PASS
	1000MHz to 2387MHz	2377.117	0.005741	2.5	PASS
	2387MHz to 2400MHz	2392.895	0.010889	25	PASS
	2483.5MHz to 2496.5MHz	2487.868	0.012972	25	PASS
	2496.5MHz to 12500MHz	12316.184	0.016672	2.5	PASS
V_{min.}	30MHz to 1000MHz	811.213	0.000106	0.25	PASS
	1000MHz to 2387MHz	1864.621	0.006887	2.5	PASS
	2387MHz to 2400MHz	2394.483	0.010447	25	PASS
	2483.5MHz to 2496.5MHz	2496.431	0.011402	25	PASS
	2496.5MHz to 12500MHz	12006.076	0.019055	2.5	PASS


TEST CHANNEL		CH 78 (2480MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASURE. VALUE(uW)	LIMIT (uW)	RESULT
V_{normal}	30MHz to 1000MHz	666.805	0.000101	0.25	PASS
	1000MHz to 2387MHz	2384.226	0.008072	2.5	PASS
	2387MHz to 2400MHz	2389.432	0.019364	25	PASS
	2483.5MHz to 2496.5MHz	2483.516	0.293765	25	PASS
	2496.5MHz to 12500MHz	6923.048	0.019724	2.5	PASS
V_{max.}	30MHz to 1000MHz	907.607	0.000096	0.25	PASS
	1000MHz to 2387MHz	2384.399	0.009376	2.5	PASS
	2387MHz to 2400MHz	2389.338	0.017620	25	PASS
	2483.5MHz to 2496.5MHz	2483.504	0.287740	25	PASS
	2496.5MHz to 12500MHz	9202.596	0.017498	2.5	PASS
V_{min.}	30MHz to 1000MHz	889.541	0.000094	0.25	PASS
	1000MHz to 2387MHz	2383.879	0.008472	2.5	PASS
	2387MHz to 2400MHz	2389.130	0.016943	25	PASS
	2483.5MHz to 2496.5MHz	2483.550	0.291743	25	PASS
	2496.5MHz to 12500MHz	10638.098	0.018707	2.5	PASS

NOTE: The spectrum plots are attached on the following pages.


Vnormal




V_{max}.




V_{min}.




Vnormal




V_{max}.




V_{min}.




Vnormal



V_{max}.



V_{min}.



4.4 Antenna Power Measurement

4.4.1 Limits of Antenna Power

Modulation System	Frequency Band Used	Antenna Power (Max.)	EIRP Limit (Note 3)
DS	2400 – 2483.5 MHz	10mW/MHz	12.14 dBm/MHz ~ 22.14 dBm/MHz (16.368 mW/MHz ~ 163.68 mW/MHz)
OFDM (Note 1)	2400 – 2483.5 MHz	10mW/MHz	12.14 dBm/MHz ~ 22.14 dBm/MHz (16.368 mW/MHz ~ 163.68 mW/MHz)
OFDM (Note 2)	2400 – 2483.5 MHz	5mW/MHz	9.13 dBm/MHz ~ 19.13 dBm/MHz (8.185 mW/MHz ~ 81.846 mW/MHz)
Other than the above	2400 – 2483.5 MHz	10mW	12.14 dBm ~ 22.14 dBm (16.368 mW ~ 163.68 mW)

Note:

1. Occupied bandwidth is less than 26MHz
2. Occupied bandwidth is more than 26MHz and less than 40MHz
3. EIRP limit is variable by the HPBA, the HPBA (half-power beam width) of the antenna shall be $360/A$ degrees or less, where $A = \text{EIRP} / (2.14 \text{ dBi} + \text{Antenna Power (limit)})$.
4. Tolerance of antenna power shall be +20% (upper value) and -80% (lower value).

4.4.2 Test Setup



4.4.3 Test Results

Voltage	Channel Number	Frequency (MHz)	Conducted RF Output Power (mW)	Radiated RF Output Power (mW)
V_{normal}	0	2402	0.893	0.281
	39	2441	0.899	0.283
	78	2480	0.700	0.220
V_{max.}	0	2402	0.883	0.278
	39	2441	0.881	0.277
	78	2480	0.675	0.212
V_{min.}	0	2402	0.914	0.288
	39	2441	0.918	0.289
	78	2480	0.728	0.229
Max. Limit (mW):			10	-
Rated Power (mW):			1	-
Tolerance of Antenna Power (mW):			0.2 ~ 1.2	-
Max. EIRP Limit (mW):			-	16.368

Note: 1. Antenna gain is -5.02 dBi.

2. The radiated RF output power is a "calculated" value derived from the conducted value.
3. Formula: Radiated RF output power = Conducted RF output power + Antenna gain

4.5 Spurious Emissions for Receiver

4.5.1 Limits of Spurious Emissions for Receiver

Frequencies (MHz)	Limit
Below 1GHz	$\leq 4\text{nW}$ (-54dBm)
Above 1GHz	$\leq 20\text{nW}$ (-47dBm)


4.5.2 Test Setup




4.5.3 Test Result

TEST CHANNEL		CH 0 (2402MHz)			
TEST CONDITION	FREQUENCY RANGE(MHz)	FREQUENCY (MHz)	MEASURE. VALUE(nW)	LIMIT (nW)	RESULT
V_{normal}	30MHz to 1000MHz	712.516	0.009795	4.0	PASS
	1000MHz to 12500MHz	11337.062	0.225424	20.0	PASS
V_{max.}	30MHz to 1000MHz	885.903	0.009506	4.0	PASS
	1000MHz to 12500MHz	11378.750	0.205116	20.0	PASS
V_{min.}	30MHz to 1000MHz	758.712	0.008630	4.0	PASS
	1000MHz to 12500MHz	10655.687	0.228560	20.0	PASS
TEST CHANNEL		CH 39 (2441MHz)			
V_{normal}	30MHz to 1000MHz	986.177	0.009247	4.0	PASS
	1000MHz to 12500MHz	10842.562	0.220800	20.0	PASS
V_{max.}	30MHz to 1000MHz	802.362	0.008492	4.0	PASS
	1000MHz to 12500MHz	2437.500	0.404576	20.0	PASS
V_{min.}	30MHz to 1000MHz	918.641	0.008770	4.0	PASS
	1000MHz to 12500MHz	11275.250	0.235505	20.0	PASS
TEST CHANNEL		CH 78 (2480MHz)			
V_{normal}	30MHz to 1000MHz	784.175	0.009204	4.0	PASS
	1000MHz to 12500MHz	11239.312	0.303389	20.0	PASS
V_{max.}	30MHz to 1000MHz	958.532	0.009376	4.0	PASS
	1000MHz to 12500MHz	2443.250	0.239883	20.0	PASS
V_{min.}	30MHz to 1000MHz	899.483	0.008730	4.0	PASS
	1000MHz to 12500MHz	10476.000	0.196789	20.0	PASS


V_{normal}



V_{max}




V_{min}




CH 0 (2402MHz)


V_{normal}



V_{max}




V_{min}




CH 39 (2441MHz)


V_{normal}



V_{max}



V_{min}




CH 78 (2480MHz)

4.6 Interference Prevention Function

4.6.1 Limits of Interference Prevention Function

Radio equipment used mainly on the same premises and automatically transmits or receives identification code.

4.6.2 Test Setup



4.6.3 Test Results

Link Mode	Test Result
Normal	Pass

5 Photographs of the Test Configuration



Appendix - Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---