







Test mode:


GFSK



2402MHz




2441MHz




2480MHz





## Test mode:

 $\pi/4$ DQPSK

## 2402MHz




## 2441MHz



## 2480MHz




## Test mode:





## 8DPSK



## 2402MHz



## 2441MHz



## 2480MHz



### 3.7. Construction protection method

#### **REQUIREMENT**

The high-frequency section and modulation section of the radio equipment except for the antenna system shall not be capable of being opened easily.

#### **CONFIRMATION METHOD**

The product has been sealed by ultrasonic technology. If you don't destroy the product, you can't open it.



### 3.8. Interference Prevention Function

#### REQUIREMENT

Clarify the one automatically to transmit and to receive identification code with the wireless equipment of the wireless station used in the same premises.

Item	Limits
Identification code	$\geq 48$ bits


#### CONFIRMATION METHOD

A communication link was made where the ID code is correct (Identical).

#### TEST PROCEDURE

1. In the case that the EUT has the function of automatically transmitting the identification code: a. Transmit the predetermined identification codes from EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code: a. Transmit the predetermined identification codes from the counterpart. b. Check if communication is normal. c. Transmit the other signals than predetermined ID codes from the counterpart. d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

#### TEST CONFIGURATION



#### TEST RESULTS

PASS

MAC Address: 6A: BC: 24: E1: BH: 92



### 3.9. Carrier Sensing Function

#### LIMIT

Item	Limits
Carrier Sense	Good - EUT stop RF transmission signal after carrier inject to EUT. (On $22.79 + Gr - 20 \cdot \log(f)$ [dBm] (Gr: dBi; f: MHz) or 100mV/m)

#### INSTRUMENTS SETTING


The following table is the setting of spectrum analyser and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1 MHz
Span	0 MHz
Sweep	Continuous
Detector	Peak
Trigger mode	Video

#### TEST PROCEDURE

- SSG adjusted the frequency as same as the EUT transmitted signal and emitted the absence of modulation from SSG and power level is (On  $22.79 + Gr - 20 \cdot \log(f)$  [dBm] (Gr: dBi; f: MHz). Then turn off the RF signal of SSG.
- EUT have transmitted the maximum modulation signal and fixed channelize.
- Setting of SA is following as: RB: 1MHz / VB: 1MHz / SPAN: 50MHz / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak.
- SSG RF Signal On.
- EUT shall be stop the transmitted any signal and SSG RF Signal Off. Then EUT will be continuous transmitted signal.

#### TEST CONFIGURATION





Report No.: HTT191011141M

**TEST RESULTS**

Page 36 of 41


Not Applicable.



Report No.: HTT191011141M

Page 37 of 41

#### 4. Test Setup Photos of the EUT





## 5. External and Internal Photos of the EUT


### External Photos of EUT






Report No.: HTT191011141M



Page 39 of 41




EUT









Internal Photos of EUT





\*\*\*\*\*THE END\*\*\*\*\*