



802.11ax (HE80)


Chain 0


TEST CONDITION	Burst Length (ms)			
	CH 42 (5210MHz)	CH 58 (5290MHz)	CH 106 (5530MHz)	CH 122 (5610MHz)
V_{normal}	5.21	5.21	5.22	5.22
$V_{max.}$	5.21	5.22	5.21	5.22
$V_{min.}$	5.22	5.22	5.22	5.21
Limit	$\leq 8ms$			


TEST CONDITION	Burst Length (ms)
	CH 138 (5690MHz)
V_{normal}	5.21
$V_{max.}$	5.22
$V_{min.}$	5.22
Limit	$\leq 8ms$














Chain 1


TEST CONDITION	Burst Length (ms)			
	CH 42 (5210MHz)	CH 58 (5290MHz)	CH 106 (5530MHz)	CH 122 (5610MHz)
V_{normal}	5.22	5.22	5.22	5.21
$V_{max.}$	5.22	5.22	5.22	5.21
$V_{min.}$	5.22	5.22	5.22	5.22
Limit	$\leq 8ms$			


TEST CONDITION	Burst Length (ms)
	CH 138 (5690MHz)
V_{normal}	5.21
$V_{max.}$	5.22
$V_{min.}$	5.21
Limit	$\leq 8ms$














Use Combiner


TEST CONDITION	Burst Length (ms)			
	CH 42 (5210MHz)	CH 58 (5290MHz)	CH 106 (5530MHz)	CH 122 (5610MHz)
V_{normal}	5.21	5.21	5.21	5.21
$V_{max.}$	5.22	5.21	5.21	5.21
$V_{min.}$	5.21	5.21	5.21	5.22
Limit	$\leq 8ms$			


TEST CONDITION	Burst Length (ms)
	CH 138 (5690MHz)
V_{normal}	5.21
$V_{max.}$	5.22
$V_{min.}$	5.21
Limit	$\leq 8ms$












4.8 Interference Prevention Function

4.8.1 Limits of Interference Prevention Function

Radio equipment used mainly on the same premises and automatically transmits or receives identification code.

4.8.2 Test Setup




4.8.3 Test Results

Link Mode	Test Result
WiFi	Pass

4.9 Carrier Sense Capability

4.9.1 Measuring System Block Diagram



4.9.2 Measuring Operation Procedures

- Turn the standard signal generator output OFF. Leave the equipment under test to be ready for transmission and verify the transmission with the spectrum analyzer.
- Set the equipment under test to the receiving state.
- Turn the standard signal generator ON and leave the equipment under test to be ready for transmission and verify with the spectrum analyzer that no transmission is being made.

4.9.3 Level of the Ambient Carrier

802.11a:

Frequency (MHz)	Pcs (dBm)	C.F (dB)	S.G Level
5180	-49.50	15.86	-33.64
5240	-49.60	15.86	-33.74
5260	-49.63	15.13	-34.50
5320	-49.73	15.32	-34.41
5500	-50.02	15.52	-34.50
5600	-50.17	15.12	-35.05
5720	-50.36	15.55	-34.81

Note:

Pcs (dBm) = 22.79 + Gr - 20log(F).

Gr: Antenna gain (5GHz W52: 2dBi, W53: 2dBi, W56: 2dBi).

F: Transmission frequency (MHz).

C.F = Distributor loss + cable loss.

802.11ax (HE20):

Frequency (MHz)	Pcs (dBm)	C.F (dB)	S.G Level
5180	-49.50	15.36	-34.14
5240	-49.60	15.69	-33.91
5260	-49.63	15.12	-34.51
5320	-49.73	15.3	-34.43
5500	-50.02	15.66	-34.36
5600	-50.17	15.19	-34.98
5720	-50.36	15.45	-34.91

Note:

Pcs (dBm) = 22.79 + Gr - 20log(F).

Gr: Antenna gain (5GHz W52: 2dBi, W53: 2dBi, W56: 2dBi).

F: Transmission frequency (MHz).

C.F = Distributor loss + cable loss.

802.11ax (HE40):

Frequency (MHz)	Pcs (dBm)	C.F (dB)	S.G Level
5190	-49.51	15.36	-34.15
5230	-49.58	15.68	-33.90
5270	-49.65	15.75	-33.90
5310	-49.71	15.86	-33.85
5510	-50.03	15.77	-34.26
5590	-50.16	15.27	-34.89
5710	-50.34	15.34	-35.00

Note:

Pcs (dBm) = 22.79 + Gr - 20log(F).

Gr: Antenna gain (5GHz W52: 2dBi, W53: 2dBi, W56: 2dBi).

F: Transmission frequency (MHz).

C.F = Distributor loss + cable loss.

802.11ax (HE80):

Frequency (MHz)	Pcs (dBm)	C.F (dB)	S.G Level
5210	-49.55	15.96	-33.59
5290	-49.68	15.58	-34.10
5530	-50.06	15.77	-34.29
5610	-50.19	15.52	-34.67
5690	-52.31	15.85	-36.46

Note:

Pcs (dBm) = 22.79 + Gr - 20log(F).

Gr: Antenna gain (5GHz W52: 2dBi, W53: 2dBi, W56: 2dBi).

F: Transmission frequency (MHz).

C.F = Distributor loss + cable loss.

4.10 Number of Carriers within 1 MHz Bandwidth in OFDM

4.10.1 Limit of Number of Carriers

For each 1MHz bandwidth in OFDM, there should be at least 1 carrier.


4.10.2 Test Setup



4.10.3 Test Results

About OFDM Technical, one OFDM Channel will have 52 sub-carriers. At present, we observe this product via the spectrum, and we know that there are 3 carriers in 1 MHz bandwidth in OFDM.

5 Photographs of the Test Configuration



Appendix - Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---