



RADIO TEST REPORT

For

SHENZHEN MAONO TECHNOLOGY CO., LTD

podcast console

Test Model: AU-AM200

Additional Model No.: Please Refer to Page 6

Prepared for : SHENZHEN MAONO TECHNOLOGY CO., LTD
Address : 401, Building 47, Software Town of Universiade, No. 8288
Longgang Rd., He'ao Community, Yuanshan Street, Longgang
District, Shenzhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : Room 101, 201, Building A and Room 301, Building C, Juji
Industrial Park, Yabianxueziwei, Shajing Street, Bao'an
District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : September 08, 2021
Number of tested samples : 1
Serial number : Prototype
Date of Test : September 08, 2021 ~ September 10, 2021
Date of Report : September 15, 2021

**RADIO TEST REPORT**
MIC Notice No.88 Appendix No. 43

Second-Generation Low-Power Data Communication System/Wireless LAN System

Report Reference No. : LCS210820099AEA

Date of Issue : September 15, 2021

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street, Bao' an District, Shenzhen, Guangdong, China

Testing Location/ Procedure..... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name : SHENZHEN MAONO TECHNOLOGY CO., LTD**

Address : 401, Building47, SoftwareTown of Universiade, No.8288 Longgang Rd., He'ao Community, Yuanshan Street, Longgang District, Shenzhen, China

Test Specification

Standard : MIC Notice No.88 Appendix No.43

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : podcast console

Trade Mark : Maono

Test Model..... : AU-AM200

Ratings..... : Input: DC 5V, 1A
DC 3.7V by Rechargeable Li-ion Battery, 1200mAhResult : **Positive****Compiled by:****Supervised by:****Approved by:**

Vera Deng/ Administrator

Jin Wang/ Technique principal

Gavin Liang/ Manager



RADIO -- TEST REPORT

Test Report No. : LCS210820099AEA	<u>September 15, 2021</u> Date of issue
------------------------------------------	--------------------------------------------

Test Model.....	: AU-AM200
EUT.....	: podcast console
Applicant.....	: SHENZHEN MAONO TECHNOLOGY CO., LTD
Address.....	401, Building47, SoftwareTown of Universiade, No.8288 Longgang Rd., He'ao Community, Yuanshan Street, Longgang District, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Guangdong Ding Chuang Manufacturing Technology Co., LTD
Address.....	Room 401, Building 8, Tian An digital city, Fenggang section 208, Dongshen road, Fenggang town, Dongguan city, Guangdong Province, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Guangdong Ding Chuang Manufacturing Technology Co., LTD
Address.....	Room 401, Building 8, Tian An digital city, Fenggang section 208, Dongshen road, Fenggang town, Dongguan city, Guangdong Province, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

**Revision History**

Revision	Issue Date	Revisions	Revised By
000	September 15, 2021	Initial Issue	Gavin Liang



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. DESCRIPTION OF DEVICE (EUT)	6
1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS	7
1.3. EXTERNAL I/O CABLE	7
1.4. DESCRIPTION OF TEST FACILITY	7
1.5. TEST CONDITIONS	7
1.6. FREQUENCY OF CHANNELS	7
2. TEST METHODOLOGY	8
2.1. EUT EXERCISE	8
2.2. MEASUREMENT UNCERTAINTY	8
2.3. TABLE FOR PARAMETERS OF TEST SOFTWARE SETTING	8
2.4. DESCRIPTION OF TEST MODES	8
2.5. TEST VOLTAGE	9
3. SYSTEM TEST CONFIGURATION	10
3.1. JUSTIFICATION	10
3.2. EUT EXERCISE SOFTWARE	10
3.3. SPECIAL ACCESSORIES	10
3.4. BLOCK DIAGRAM/SCHEMATICS	10
3.5. EQUIPMENT MODIFICATIONS	10
4. SUMMARY OF TEST RESULTS	11
5. TEST RESULT	12
5.1. FREQUENCY TOLERANCE	12
5.2. ANTENNA POWER	13
5.3. OCCUPIED FREQUENCY BANDWIDTH	14
5.4. SPREAD BANDWIDTH	15
5.5. TRANSMITTER SPURIOUS EMISSIONS (CONDUCTED)	16
5.6. SECONDARY RADIATED EMISSIONS	17
5.7. DWELL TIME	18
5.8. CARRIER SENSING FUNCTION	19
5.9. INTERFERENCE PREVENTION FUNCTION	20
6. PHOTOGRAPHS OF TEST SETUP	21
7. EXTERNAL PHOTOGRAPHS OF THE EUT	21
8. INTERNAL PHOTOGRAPHS OF THE EUT	21
9. LIST OF MEASURING EQUIPMENTS	21



1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: podcast console
Test Model	: AU-AM200
Additional Model No.	: AU-AM200-S1, AU-AM200-S2, AU-AM200-S3, AU-AM200-S4, AU-AM200-S5, AU-AM200-S6
Model Declaration	: PCB board, structure and internal of these model(s) are the same, So no additional models were tested
Power Supply	: Input: DC 5V, 1A DC 3.7V by Rechargeable Li-ion Battery, 1200mAh
Hardware Version	: Mainboard: CSX-AM200-PCB 20200901 Module: CSX-AC6901 20200819
Software Version	: V1.0
Bluetooth	
Frequency Range	: 2402-2480MHz for Bluetooth (79 channels for Bluetooth V5.0(BDR/EDR) Channel Frequency=2402+(K-1), K=1, 2, 379
Declared Antenna Power	: Bluetooth V5.0(BDR/EDR): 0.02mW/MHz
Modulation Technology	: Bluetooth V5.0(BDR/EDR): GFSK, $\pi/4$ -DQPSK
Data Rate	: Bluetooth V5.0(BDR/EDR): 1/2Mbps
Antenna Description	: PCB Antenna, -0.58dBi(Max.)



1.2. Host System Configuration List and Details

Manufacturer	Description	Model	Serial Number	Certificate
--	--	--	--	--

1.3. External I/O Cable

I/O Port Description	Quantity	Cable
Type-C Port	1	N/A
POD OUTPUT Port	3	N/A
OUTPUT Port	1	N/A
MUSIC INPUT Port	1	N/A
Headset Port	1	N/A
MIC Port	2	N/A

1.4. Description of Test Facility

FCC Registration Number is 254912.

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Industry Canada Registration Number is 9642A.

1.5. Test Conditions

Temperature Range	:	21-25℃
Humidity Range	:	45-85%
Pressure Range	:	86-106kPa

1.6. Frequency of Channels

Bluetooth V5.0 (BDR/EDR)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2402	41	2442
2	2403	42	2443
--	--	--	--
38	2439	78	2479
39	2440	79	2480
40	2441		



2. TEST METHODOLOGY

2.1. EUT Exercise

The EUT was tested while in a continuous transmitter/receiver mode.

The EUT was tuned to a low, middle, and high channel for the purpose of the measurements.

For all test case pre/scans were completed in all Modes to determine worst case levels.

According to its specifications, the EUT must comply with the requirements of MIC Notice No.88 Appendix No. 43.

2.2. Measurement Uncertainty

Test Item		MU	Remark
Bandwidth	:	+/- 0.2 E-6	/
Antenna Power	:	+/-0.33dB	/
Frequency Tolerance	:	+/- 0.3 E-6	/
Conducted spurious emission	:	+/-0.13dB	/
DC Power	:	+/-1%	/

- (1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.3. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters:

Test Software Version	The sample will be controlled by dialing FCC Assist 2.4 to enter RF test mode to control sample		
Frequency	2402MHz	2441MHz	2480MHz
Bluetooth V5.0	Default	Default	Default

2.4. Description of Test Modes

Tested channel, Frequency and Modulation Information		
CH1	2402MHz	GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps)
CH40	2441MHz	GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps)
CH79	2480MHz	GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps)
Hopping Mode		GFSK(1Mbps), $\pi/4$ -DQPSK(2Mbps)
Note: According exploratory test, EUT has maximum output power for GFSK modulation, All the test modes were tested, but only the worst case was recorded in this report.		



2.5. Test Voltage

POWER SUPPLY VOLTAGE FLUCTUATION TEST

Voltage Fluctuation Test	Normal Voltage	High Voltage +10% of Normal Voltage	Low Voltage -10% of Normal Voltage
Input To EUT	DC 5V	DC 5.5V	DC 4.5V
Output To RF Module	DC 3.3V	DC 3.3V	DC 3.3V
Voltage Variation (%)	--	--	--

Note:

As declared by the manufacturer, the AP8248A regulates the DC power to be DC 3.3V and supply to the RF module.

Voltage Variation (%) = (Output high or Low Voltage - Output Normal Voltage) / Output Normal Voltage * 100

During the input supply voltage to the EUT from the external power source is varied by +/- 10%, if output voltage had been confirmed that the fluctuation of power supply to the RF circuit of EUT (excluding power source) is equal to or less than +/-1%. Exempt extremely high and low supply voltage condition test, EUT only operated in normal voltage to test all regulations.



3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a typical fashion.

3.2. EUT Exercise Software

N/A.

3.3. Special Accessories

N/A.

3.4. Block Diagram/Schematics

Please refer to the report.

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.



4. SUMMARY OF TEST RESULTS

MIC Notice No.88 Appendix No.43 Article 2 Paragraph 1 Item 19		
Clause	Description of Test (Transmitter Parameters)	Result
3	Frequency Tolerance	PASS
6	Antenna Power	PASS
6	Tolerances for Antenna Power	PASS
4	Transmission Rate	PASS
4	Occupied Frequency Bandwidth	PASS
4	Spread Bandwidth	PASS
13	Dwell Time	PASS
5	Spurious Emissions	PASS
10	Transmission Antenna Gain (EIRP Antenna Power)	N/A
11	Transmission Radiated Angle Width (3dB Beam width)	N/A
12	Interference prevention function	PASS
8	Carrier Sensing function	N/A
Receiver Parameters		
7	Secondary Radiated Emissions	PASS
(1) N/A is an abbreviation for Not Applicable.		



5. TEST RESULT

5.1. Frequency Tolerance

5.1.1. Standard Applicable

Tolerance of frequency shall be ± 50 ppm.

5.1.2. Test Procedures

- Set EUT work in test mode as described in clause 2.4.
- Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 10 KHz.

Video BW: 10 KHz.


Span: 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

- When the trace is complete, find the peak value of the power envelope and record.

5.1.3. Test Setup Layout



5.1.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.5. Test Result

Please refer to the Appendix A.1 for BT Test Data.



5.2. Antenna Power

5.2.1. Standard Applicable

Type	Limit
Antenna Power	3mW/MHz
Tolerance	+20%, -80%


5.2.2. Measuring Instruments

Please refer to section 6 of equipments list in this report.

5.2.2. Test Procedures

- EUT have transmitted continuous maximum power
- Antenna Power Error is definition that actual measure antenna power tolerance between +20% to -80% power range that base on manufacturer declare the conducted power density.

5.2.3. Test Setup



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result

Please refer to the Appendix A.2 for BT Test Data.



5.3. Occupied Frequency Bandwidth

5.3.1. Standard Applicable

Permissible value for occupied bandwidth using the FH system, a hybrid system combining DS and FH systems, or a hybrid system combining FH and OFDM systems shall be 83.5 MHz or less, while necessary bandwidth (minimum occupied bandwidth sufficient to ensure information transmission of required quality at a required transmission rate for the system used under specified conditions for a given emission type) using a system other than any of the above shall be 26 MHz or less.

5.3.2. Test Procedures

- Set EUT work in test mode as described in clause 2.4.
- Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 1MHz.

Video BW: 1MHz.

Span: Wide enough to cover the complete power envelope of the signal of the EUT.


Sweep mode: Continuous sweeping.

Detector: Peak.

Trace Mode: Max Hold.

- When the trace is complete, measure the occupied bandwidth (99% bandwidth) with spectrum analyzer's bandwidth measure function.

5.3.3. Test Setup Layout



5.3.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.3.5. Test Result of Occupied Bandwidth

Please refer to the Appendix A.3 for BT Test Data.



5.4. Spread Bandwidth

5.4.1. Standard Applicable

In spread spectrum systems, spread bandwidth (which refers to a frequency bandwidth with an upper limit and lower limit such that each of the mean powers radiated above the upper frequency limit and below the lower frequency limit is equal to 5 % of the total mean power radiated; this also applies hereafter) shall be 500 kHz or more.

The OFDM system shall have one or more carriers per 1 MHz bandwidth.

5.4.2. Test Procedures

- Set EUT work in test mode as described in clause 2.4.
- Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 1MHz.

Video BW: 1MHz.


Span: Wide enough to cover the complete power envelope of the signal of the EUT.

Detector: Peak.

Trace Mode: Max Hold.

- When the trace is complete, measure the spread bandwidth (90% bandwidth) with spectrum analyzer's bandwidth measure function.

5.4.3. Test Setup Layout



5.4.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.4.5. Test Result of Spectrum Bandwidth

Please refer to the Appendix A.4.1 for BT Test Data.

5.4.6. Test Result of Spread Spectrum Factor

Please refer to the Appendix A.4.2 for BT Test Data.



5.5. Transmitter Spurious Emissions (conducted)

5.5.1. Standard Applicable

Permissible mean power of spurious emission of each frequency supplied to a feeder, that is, mean power of spurious emission in the 1 MHz bandwidth at frequency f other than frequency band used shall be as follows:

- | | |
|----------------------------------------------------|----------------------|
| a. 30MHz – 1,000MHz | 0.25 μ W or less |
| b. 1,000MHz – 2,387MHz | 2.5 μ W or less |
| c. 2,387MHz – 2,400MHz and 2,483.5MHz – 2,496.5MHz | 25 μ W or less |
| d. 2,496.5MHz – 12.5GHz | 2.5 μ W or less |

5.5.2. Test Procedures

- Set EUT work in test mode as described in clause 2.4.
- Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Below 1GHz: RBW/VBW= 100KHz/ 100KHz


Above 1GHz: RBW/VBW= 1MHz / 1MHz.

Detector: Peak.

Trace Mode: Max Hold.

- All the emissions from 30MHz to 13GHz were measured and record.

5.5.3. Test Setup Layout



5.5.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.5. Test Results

Please refer to the Appendix A.5 for BT Test Data.



5.6. Secondary Radiated Emissions

5.6.1. Standard Applicable

The limit on secondary emissions radiated from the receiving equipment within which the function of other radio equipment will not be impaired shall be, in terms of the power of a dummy antenna circuit that has the same electrical constant as the receiving antenna, 4nW or less at a frequency below 1 GHz and 20nW or less at a frequency of 1 GHz or higher as measured using the circuit

5.6.2. Test Procedures

- Set EUT work in test mode as described in clause 2.4.
- Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Resolution BW: 100 KHz for frequency below 1GHz and

1MHz for frequency above 1GHz

Video BW: 100 KHz for frequency below 1GHz and


1MHz for frequency above 1GHz

Detector: Peak.

Trace Mode: Max Hold.

- All the emissions from 30MHz to 13GHz were measured and record.

5.6.3. Test Setup



5.6.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.6.5. Test Results

Please refer to the Appendix A.6 for BT Test Data.



5.7. Dwell Time

5.7.1. Standard Applicable

Frequency dwell time (time during which radio waves continue to be emitted at a specified frequency) of a transmitting equipment using the FH system shall be 0.4 seconds or less.

5.7.2. Test Procedures

- Set EUT work in test mode as described in clause 2.4.
- Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the channel under test.

Resolution BW: 1MHz.

Video BW: 1MHz.


Span: Zero MHz

Detector: Peak.

Trace Mode: Max Hold.

- When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

5.7.3. Test Setup Layout



5.7.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.7.5. Test Results

Please refer to the Appendix A.7 for BT Test Data.



5.8. Carrier sensing function

5.8.1. Standard Applicable

Item	Limits
Carrier Sense	Good – EUT stop RF transmission signal after carrier inject to EUT. (On $22.79 + Gr - 20 \cdot \log(f)$ [dBm] (Gr: dBi; f: MHz) or 100mV/m)

5.8.2. Instruments Setting


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
RB / VB	1 MHz
Span	0 MHz
Sweep	Continuous
Detector	Peak
Trigger mode	Video

5.8.3. Test Procedures

1. SSG adjusted the frequency as same as the EUT transmitted signal and emitted the absence of modulation from SSG and power level is (On $22.79 + Gr - 20 \cdot \log(f)$ [dBm] (Gr: dBi; f: MHz). Then turn off the RF signal of SSG.
2. EUT have transmitted the maximum modulation signal and fixed channelize.
3. Setting of SA is following as: RB: 1MHz / VB: 1MHz / SPAN: 50MHz / AT: 10dB / Ref: 0dBm / Sweep time: Auto / Sweep Mode: Continuous sweep / Detect mode: Positive peak.
4. SSG RF Signal On.
5. EUT shall be stop the transmitted any signal and SSG RF Signal Off. Then EUT will be continuous transmitted signal.

5.8.4. Test Setup Layout



5.8.5. EUT Operation during Test

The EUT was programmed to be in normal transmitting mode.

5.8.6. Test Result

Not Applicable.



5.9. Interference prevention function

5.9.1. Standard Applicable

Item	Limits
Identification code	≥ 48 bits


5.9.2. Measuring ID Code Software

PC with NetTool	Setting
MAC IP List	MAC Scan

5.9.3. Test Procedures

1. In the case that the EUT has the function of automatically transmitting the identification code:
 - a. Transmit the predetermined identification codes from EUT. b. Check the transmitted identification codes with the demodulator.
2. In the case of receiving the identification code:
 - a. Transmit the predetermined identification codes from the counterpart. b. Check if communication is normal. c. Transmit the other signals than predetermined ID codes from the counterpart. d. check if the EUT stops the transmission, or if it displays that identification codes are different from the predetermined ones.

5.9.4. Test Setup Layout



5.9.5. EUT Operation during Test

The EUT was programmed to be in normal transmitting mode.

5.9.6. Test Result

EUT ID	Performance index
60:ab:67:f0:90:fc	Good



6. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files Appendix B for Test Setup Photographs

7. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix C for External Photos of EUT

8. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files Appendix D for Internal Photos of EUT

9. LIST OF MEASURING EQUIPMENTS

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	Rohde & Schwarz China	NRVS	100444	2021-06-21	2022-06-20
2	Power Sensor	Rohde & Schwarz China	NRV-Z81	100458	2021-06-21	2022-06-20
3	Power Sensor	Rohde & Schwarz China	NRV-Z32	10057	2021-06-21	2022-06-20
4	MXA Signal Analyzer	Agilent Technologies Inc.	N9020A	MY49100060	2020-11-17	2021-11-16
5	DC Power Supply	Agilent Technologies Inc.	E3642A	N/A	2020-11-13	2021-11-12

Note: All equipment is calibrated through CCIC(Shenzhen) Metrology & Testing Service Co.,Ltd.

-----THE END OF REPORT-----